

# PRODUCT DATASHEET OT CABLE CLAMP B-STYLE TL

OPTOTRONIC® Cable Clamp | Driver accessories



## Areas of application

- Downlights, flat luminaires
- Suitable for different cable types
- Suitable for indoor installations

#### Product benefits


- Simple and quick cable mounting
- Sufficient space for cable connection
- Cost-effective and space-saving solution (TL version)
- Free cable connection thanks to open flaps
- Immediate installation thanks to pre-assembled cable clamps

## **Product features**

- Easy to install and flexible cable clamps
- Separate cable clamps for primary and secondary side
- Pre-fixed, captive screws
- Through-looping (TL version)

## TECHNICAL DATA

# Dimensions & Weight



Length	90.0 mm
Width	92.0 mm
Height	29.5 mm
Product weight	80.00 g

# Temperatures & operating conditions

Max.housing temperature in case of fault	110 °C
Permitted rel. humidity during operation	585 % 1)

<sup>1)</sup> Maximum 56 days/year at 85 %

## Certificates & Standards

Type of protection	IP20

## LOGISTICAL DATA

|--|

## DOWNLOAD DATA

	Documents and certificates	Document name
PDF	User instruction / safety instructions	547465_OT Cable Clamp TL-B Instructions sheet

	CAD/BIM files	Document name
STEP .	CAD STEP 3D	CC_B-Style-TL

	CAD/BIM files	Document name
ZIP	CAD data 3D PDF	CAD data PDF OT Cable Clamp B-Style TL

## LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4052899948051	Unpacked 1		80.00 g	
4052899268227	Shipping box 20	470 mm x 188 mm x 68 mm	1788.00 g	6.01 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.