

PRODUCT DATASHEET

MS-SV MIC-CS 360 220-240 V IP20

LED VALUE Microwave Motion Sensor | Sensors with microwave technology



Areas of application

- Suitable for indoor applications.
- Offices
- Corridors
- Stairways
- Residential interiors
- Commercial buildings

Product features

- 360° motion sensor (microwave technology)
- Ceiling surface and recessed mounting
- Timer function
- Adjustable illuminance from 3 or 10 lx to 2000 lx via knob switch (model dependent)
- Photocell detector available for daylight detection
- Operating frequency: 50/60 Hz
- Ambient temperature in operation: -35...+50 °C
- Type of protection: IP20

TECHNICAL DATA

Electrical data

Nominal voltage	220...240 V
Type of current	AC
Mains frequency	50...60 Hz

Dimensions & Weight

Length	108.00 mm
Width	108.00 mm
Height	25.00 mm
Product weight	97.00 g

Colors & materials

Product color	White
---------------	-------

Temperatures & operating conditions

Ambient temperature range	-35...+50 °C
---------------------------	--------------

Capabilities

Dimmable	No
Maximum installation height	2.2...4 m
Detection area	8 m ¹⁾
Detection angle	360 °

¹⁾ Maximum diameter

Certificates & Standards

Protection class	II
Type of protection	IP20

LOGISTICAL DATA

Temperature range at storage	-35...+55 °C
------------------------------	--------------

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075373075	Folding box 1	115 mm x 36 mm x 120 mm	114.00 g	0.50 dm ³
4058075373082	Shipping box 10	242 mm x 192 mm x 140 mm	1351.00 g	6.50 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products.

When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.