

## PRODUCT DATASHEET DALIECO BT CONTROL

DALieco BT CONTROL | Control units for light management systems



### Areas of application

- Floor-standing luminaires
- Meeting rooms
- Conference rooms
- Training rooms
- Classrooms
- Corridors
- Shop lighting

### Product benefits

- Control the light via Smartphone
- Adjustment of all settings via smartphone
- Plug and Play: Basic features usable without App
- Simplified startup thanks to predefined operation modes
- Intuitive manual dimming, switching and changing of colour temperature
- Up to 4 groups separately controllable
- Adjustable Offset for different groups
- Easy Scene creation via App
- Scene-recall via OSRAM DALI PRO PB coupler possible
- Firmware update over-the-air via Bluetooth possible
- Integrated DALI supply
- Control of standard white or Tunable White light acc. DALI device type 8 (DT8)\*
- Selected DALI parameters changeable via APP

### Product features

- Compact light control with DALI interface
- Smart phone connection via Bluetooth to control and configure
- One DALI output channel (Broadcast or Groupcast)
- Up to 32 DALI luminaires connectable
- Supports up to 4 OSRAM DALI sensors and pushbutton couplers


- Daylight-dependent regulation and presence-dependent control of light
- Separate pushbutton input to operate via standard pushbutton
- Supports DALI DT8 Tunable White driver
- Outputs with electronical reversible overtemperature, short-circuit, overload protection
- Length of the DALI control cable: up to 300 m
- Length of the pushbutton cable: up to 50 m
- Suitable for luminaire integration

## TECHNICAL DATA

### Electrical data

Nominal wattage	3.00 W
Nominal voltage	230 V
Mains frequency	50/60 Hz
Operating frequency	50/60 Hz

### Dimensions & Weight



Length	108.00 mm
Width	31.00 mm
Height	21.00 mm
Product weight	45.00 g

### Temperatures & operating conditions

Ambient temperature range	-20...+60 °C
---------------------------	--------------

### Additional product data

Number of control outputs	1
Number of connectable sensors	4
Max. connectable push button couplers / sensors	4
Commissioning App	App (Android/ iOS)
Groups	4

### Capabilities

Dimmable	No
Dimming interface	DALI
Number of control outputs	1
Type of installation	Luminaire integration/Independent mounting
Transmitter range	15 m

### Certificates & Standards







Approval marks – approval	CE
Protection class	II



Type of protection	IP20
--------------------	------

## EQUIPMENT / ACCESSORIES

- Free App for iOS and Android available at the app store
- Ceiling or independent installation via ECO CI KIT possible

## DOWNLOAD DATA

Documents and certificates		Document name
	User instruction / safety instructions	DALleco BT control
	User instruction / safety instructions	DALIECO BT CONTROL
	User instruction / safety instructions	DALleco BT control Mounting instruction
	Declarations of conformity	DALleco BT RTC
	Declarations of conformity UKCA	DALIECO BT RTC CONTROL
	Certificates	VDE

CAD/BIM files		Document name
	CAD STEP 3D	OT FIT 120 D LT2 L STEP 270220
	CAD STEP 3D	DALIECO BT RTC CONTROL STEP 220120

## LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4052899988781	Folding box 1	160 mm x 35 mm x 40 mm	75.00 g	0.22 dm <sup>3</sup>
4052899988798	Shipping box 25	223 mm x 197 mm x 179 mm	2006.00 g	7.86 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.