

PRODUCT DATASHEET LS/PD MULTI3 CI

LS/PD MULTI 3 CI | Light and presence sensor, recessed ceiling, moveable



Areas of application

- Offices
- Corridors
- Classrooms
- Training rooms
- Stairways
- Sanitary areas

Product benefits

- Particularly small construction

Product features

- Ceiling installation sensor with moveable sensor head
- Connection via four-pole screw terminal or modular 4c4p-connector

TECHNICAL DATA

Electrical data

Mains frequency	0 Hz
-----------------	------

Dimensions & Weight

Length	50.00 mm
Width	50.00 mm
Height	25.00 mm
Diameter	50,0 mm
Product weight	30.00 g

Colors & materials

Product color	White
---------------	-------

Temperatures & operating conditions

Ambient temperature range	0...+50 °C
---------------------------	------------

Capabilities

Dimmable	No
Maximum installation height	4 m
Detection area	6 m ¹⁾
Detection angle	80 ° ²⁾
Type of installation	On-top ceiling mounting/Ceiling integration
Operating range, light sensor	20...600 lx ³⁾

1) Maximum diameter

2) Approximately

3) Approximately, measured at the sensor



Certificates & Standards

Approval marks – approval	CE
Protection class	III
Type of protection	IP20

EQUIPMENT / ACCESSORIES

- Surface mounting in connection with SENSOR KIT
- Suitable for MULTleco, DIM MULTleco, DALI MULTleco control unit
- Suitable for DALI Professional Sensor Coupler

DOWNLOAD DATA


Documents and certificates	Document name
 User instruction / safety instructions	334180_LS/PD MULTI 3 CI – light and presence sensor for ceiling installation
 Declarations of conformity	334067_LMS MULTI3 SENSORS

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4008321916648	Folding box 1	170 mm x 34 mm x 91 mm	93.00 g	0.53 dm ³
4008321916655	Shipping box 10	245 mm x 188 mm x 204 mm	961.40 g	9.40 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

ADDITIONAL CATALOG INFORMATION



h	20 m	25 m	30 m	4.0 m	5.0 m
A	25 m	33 m	4.0 m	5.0 m	—
B	45 m	53 m	6.0 m	7.0 m	7.0 m

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.