

## PRODUCT DATASHEET

### DALI PRO PB Coupler

DALI PRO PB Coupler | Control units for light management systems



#### Areas of application

- Classrooms
- Conference rooms
- Suitable for installation in flush-type boxes
- Production and assembly facilities
- Individual offices

#### Product benefits

- Power supply from DALI
- Standard pushbuttons/switches can be used

#### Product features


- DALI pushbutton coupler
- 4 floating inputs

## TECHNICAL DATA

### Electrical data

Nominal wattage	1.00 W
Nominal voltage	20 V
Mains frequency	0 Hz

### Dimensions & Weight



Length	42.00 mm
Width	42.00 mm
Height	20.00 mm
Product weight	22.00 g

### Temperatures & operating conditions

Ambient temperature range	0...+50 °C
---------------------------	------------

### Additional product data

Number of control outputs	1
---------------------------	---

### Capabilities

Dimmable	No
Dimming interface	DALI
Number of control outputs	1



### Certificates & Standards

Protection class	II
Type of protection	IP20

## EQUIPMENT / ACCESSORIES

- Can be used with DALI Professional or DALIeco light control system

## DOWNLOAD DATA

Documents and certificates		Document name
	User instruction / safety instructions	334697_Technical instructions
	Declarations of conformity	334811_Declaration of conformity – DALI PRO CONT-4 – DALI PRO PB Coupler – DALI PRO Sen

## LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4008321496461	Folding box 1	93 mm x 40 mm x 80 mm	43.00 g	0.30 dm <sup>3</sup>
4008321543134	Shipping box 20	255 mm x 166 mm x 258 mm	1033.00 g	10.92 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.