

# PRODUCT DATASHEET DALI Sensor Coupler HF LS LI

DALI Sensor Coupler HF LS LI | Sensors for light management systems



#### Areas of application

- Connection of light and presence sensors in DALI systems
- Ceiling or independent installation via ECO CI KIT possible
- Luminaire and ceiling integration
- Installation in industry and office luminaires
- Installation in IP protected luminaires possible
- Areas with high ceilings

#### Product benefits

- Sensor integration in DALI
- Small housing design

#### **Product features**


- Mounting height: 2...13 m
- Combined daylight and motion detection
- Suitable for daylight-dependent control
- Presence detection via active radar sensor element
- Light sensor operating range: 20...800 lx (measured at sensor)

## **TECHNICAL DATA**

## Electrical data

Nominal wattage	0.45 W
Nominal voltage	230 V
Mains frequency	50 Hz

# Dimensions & Weight



Length	118.00 mm
Mounting hole spacing, length	110,0 mm
Width	30.00 mm
Height	21.00 mm
Product weight	50.00 g

# Temperatures & operating conditions

Ambient temperature range	0+50 °C

# Additional product data

Number of control outputs		1
---------------------------	--	---

# Capabilities

Dimmable	No	
Dimming interface	DALI	
Type of installation	Luminaire integration/Ceiling integration	

## Certificates & Standards

Approval marks – approval	CE
Protection class	II
Type of protection	IP20

# **EQUIPMENT / ACCESSORIES**

- Separate installation possible with ECO CI KIT
- Suitable for many OSRAM DALI control systems

## DOWNLOAD DATA

	Documents and certificates	Document name	
PDF	User instruction / safety instructions	538505_Manual DALI Sensor Coupler HF LS LI	
PDF	User instruction / safety instructions	DALI Sensor Coupler HF LS LI	
PDF	Declarations of conformity	538499_CE declaration DALI Professional System	
PDF	EU Data Act	Connected Products and Related Software and Services	
	CAD/BIM files	Document name	
PDF	CAD data 3D PDF	DALI Sensor Coupler CAD pdf	

## LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4052899141728	Folding box 1	128 mm x 37 mm x 27 mm	64.00 g	0.13 dm <sup>3</sup>
4052899141735	Shipping box 25	200 mm x 140 mm x 147 mm	1617.00 g	4.12 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.