

# PRODUCT DATASHEET

## LS VAL -500/RGB/5

LED STRIP VALUE-500 RGB | RGB LED strips with 500 lm/m for general applications



### Areas of application

- Effect lighting in architecture
- Dynamic effects in public zones
- Cove lighting
- Under-cabinet lighting
- Hotels and Offices
- Residential interiors

### Product benefits

- Great scope of design options due to long and flexible RGB LED strips
- Uniform color changing
- Easy installation, no tools required for connection
- Easy mounting on many smooth surfaces thanks to self-adhesive tape
- Maximum flexibility due to large range of accessories
- Simple connection thanks to integrated cables on both sides

### Product features

- Flexible and splittable LED strip with inline multichip RGB LEDs
- Smallest cuttable unit: 100 mm
- Lifetime (L70/B50): up to 40,000 h at Tc max.: 75°C
- Dimmable by pulse width modulation (PWM)



## TECHNICAL DATA

### Electrical data

Nominal wattage	67.00 W
Construction wattage	67.00 W
Nominal wattage per meter	14.4 W <sup>1)</sup>
Nominal voltage	24 V <sup>2)</sup>
Input voltage range	23...25 V <sup>2)</sup>
Reverse Voltage	27 V <sup>2)</sup>
Type of current	DC
Nominal current	2800 mA

1) Value based on first meter of the product

2)  $V_{DC}$

### Photometrical data

Luminous efficacy	37.2 lm/W <sup>1)</sup>
Luminous flux	2400 lm
Luminous flux per meter	535 lm <sup>1)</sup>
Luminous flux per module chain	2400 lm
Luminous flux per meter - Red	106 lm/m <sup>1)</sup>
Luminous flux per meter - Green	325 lm/m <sup>1)</sup>
Luminous flux per meter - Blue	73 lm/m <sup>1)</sup>
Luminous flux per meter - RGB	535 lm/m <sup>1)</sup>
Light color LED	RGB
Light color (designation)	RGB

1) Value based on first meter of the product


### Light technical data

Beam angle	120 °
Rated beam angle (half peak value)	120.00 °

### LED MODULE INFORMATION

Number of LEDs per meter	60
Number of LEDs per module	300
Number of LEDs per smallest unit	6

## Dimensions & Weight



Length	5000.00 mm
Length – smallest unit	100 mm
Cable length	500.000
Width	10.00 mm
Height	2.20 mm
Prewired	Yes
Conductor cross section	0.5 mm <sup>2</sup>
LED pitch	16.7 mm
Short pitch	No
Product weight	110.00 g

## Temperatures & operating conditions

Ambient temperature range	-20...+45 °C <sup>1)</sup>
Maximum temperature at tc test point	75 °C <sup>2)</sup>

1) Providing that temperature at Tc point is below max value during operation

2) Exceeding the maximum specified ratings can reduce expected life time or destroy the LED strip

## Lifespan

Nominal lamp life time	40000 h
------------------------	---------

## Capabilities

Dimmable	Yes <sup>1)</sup>
Lowest bending radius	30 mm
Self-adhesive	Yes

1) Dimmable with suitable drivers, see also [www.ledvance.com/dim](http://www.ledvance.com/dim)

## Certificates & Standards





Approval marks – approval	RoHS / CE / REACH
Protection class	III
Type of protection	IP00

Salt mist resistance acc. IEC 60068-2-52	No
UV resistance acc. IEC 60068-2-5	No












**LOGISTICAL DATA**












Temperature range at storage	-20...+85 °C
------------------------------	--------------









**Accessories Mandatory**

Product image	Product name	EAN
	DR-PFM -150/220-240/24/P	4058075239975
	DR-PFM -250/220-240/24/P	4058075240032
	DR-VAL -150/220-240/24	4058075240179
	DR-VAL -120/220-240/24	4058075240131
	DR DIM-PFM -150/220-240/24/P	4058075240117
	DR DIM-PFM -100/220-240/24/P	4058075240070
	DR-PFM -100/220-240/24/P	4058075239937
	DR DIM-PFM -250/220-240/24/P	4058075240155

**Accessories Optional**

Product image	Product name	EAN
	LS AY -PF04/U/17X7/12/1	4058075278288
	LS AY -PW02/UW/39X26/14/1	4058075278134
	LS AY -PM03/E/19X19/10/2	4058075401716
	LS AY -PM06/E/18X18/12/2	4058075401808
	LS AY -PM02/R/18X15,5/10/2	4058075401686
	LS AY -PW01/U/26X8/14/1	4058075278103
	LS AY -PM01/UW/21,5X12/10/1	4058075278318
	LS AY -PM03/E/19X19/10/1	4058075278370
	LS AY -PF02/U/16X5/10/2	4058075401563
	LS AY -PF04/U/17X7/12/2	4058075401624
	LS AY VAL -CSD/P4	4058075407831


Product image	Product name	EAN
	LS AY -PM04/UW/23X15,5/10/1	4058075278400
	LS AY -PW03/U/26X26/14/1	4058075278165
	LS AY -PM06/E/18X18/12/1	4058075279308
	LS AY -PM04/UW/23X15,5/10/2	4058075401747
	LS AY -PF01/UW/22X6/10/1	4058075278196
	LS AY -PM01/UW/21,5X12/10/2	4058075401655
	LS AY -PM02/R/18X15,5/10/1	4058075278349
	LS AY -PM05/U/17,5X14,5/10/2	4058075401778
	LS AY VAL -12/SMB	4058075411708
	LS AY -PW01/U/26X8/14/2	4058075401440
	LS AY -PF01/UW/22X6/10/2	4058075401532


















Product image	Product name	EAN
	LS AY -PW03/U/26X26/14/2	4058075401501
	LS AY -PF03/UW/25X7/12/2	4058075401594
	LS AY VAL -CSW/P4/50	4058075407862
	LS AY VAL -CP/P4/500	4058075407800
	LS AY -PF02/U/16X5/10/1	4058075278226
	LS AY -PW02/UW/39X26/14/2	4058075401471
	LS AY -PF03/UW/25X7/12/1	4058075278257
	LS AY -PM05/U/17,5X14,5/10/1	4058075279278

**Safety advice**


– All electrical connections must be made by a qualified person.

**DOWNLOAD DATA**

Documents and certificates	Document name
 User instruction / safety instructions	LED STRIP VALUE RGB IP00

Documents and certificates		Document name
	Declarations of conformity	LS VAL RGB
Photometric and lighting design files		Document name
	IES file (IES)	LS VAL-500-RGB-5-1M-RGB_IESNA2002
	IES files (IES, additional)	LS VAL-500-RGB-5-1M-Blue_IESNA2002
	IES files (IES, additional)	LS VAL-500-RGB-5-0.1M-Red_IESNA2002
	IES files (IES, additional)	LS VAL-500-RGB-5-0.1M-Blue_IESNA2002
	IES files (IES, additional)	LS VAL-500-RGB-5-1M-Red_IESNA2002
	IES files (IES, additional)	LS VAL-500-RGB-5-1M-Green_IESNA2002
	IES files (IES, additional)	LS VAL-500-RGB-5-0.1M-Green_IESNA2002
	IES files (IES, additional)	LS VAL-500-RGB-5-0.1M-RGB_IESNA2002
	LDT file (Eulumdat)	LS VAL-500-RGB-5-1M-RGB
	LDT files (Eulumdat, additional)	LS VAL-500-RGB-5-1M-Red
	LDT files (Eulumdat, additional)	LS VAL-500-RGB-5-1M-Green
	LDT files (Eulumdat, additional)	LS VAL-500-RGB-5-0.1M-RGB
	LDT files (Eulumdat, additional)	LS VAL-500-RGB-5-0.1M-Blue
	LDT files (Eulumdat, additional)	LS VAL-500-RGB-5-1M-Blue
	LDT files (Eulumdat, additional)	LS VAL-500-RGB-5-0.1M-Red
	LDT files (Eulumdat, additional)	LS VAL-500-RGB-5-0.1M-Green



Tender texts	Document name
 Tender documents	LED STRIP VALUE 500 RGB 500 RGB 5-EN

**LOGISTICAL DATA**

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075404441	Folding box 1	242 mm x 242 mm x 26 mm	301.00 g	1.52 dm <sup>3</sup>
4058075404458	Shipping box 10	260 mm x 260 mm x 265 mm	3401.00 g	17.91 dm <sup>3</sup>
4058075404465	Shipping box 40	540 mm x 280 mm x 555 mm	13604.00 g	83.92 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

**DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.