

PRODUCT DATASHEET

LM SPOT 111-4300-840-40D

LED MODULE SPOT 111 | LED modules



Areas of application

- Suitable for indoor applications.
- Chain stores, retail shops
- Shopping centers
- Museums
- Decorative lighting
- Exhibition halls

Product features

- Fits into standard R111 luminaires
- Available with color temperature: 3,000 K, 4,000 K, 6,500 K
- Available with beam angle: 24°, 40°, 60°
- Available with luminous flux: 2,700 lm, 4,300 lm
- Lifetime (L70/B50): 50,000 h
- Compatible with constant current LED driver



TECHNICAL DATA

Electrical data

Nominal wattage	36.00 W
Construction wattage	36.00 W
Nominal voltage	30 V
Type of current	DC
Nominal current	1050.000 mA

Photometrical data

Luminous efficacy	120 lm/W
Luminous flux	4300 lm
Color temperature	4000 K
Color rendering index Ra	≥80
Light color (designation)	Cool White
Standard deviation of color matching	≤3 sdcn

Light technical data

Beam angle	40 °
------------	------

Dimensions & Weight

Length	111.00 mm
Width	111,0 mm
Height	57.00 mm
Diameter	111,0 mm
Product weight	400.00 g

Temperatures & operating conditions

Ambient temperature range	-20...+45 °C
Maximum temperature at tc test point	85 °C

Lifespan

Nominal lamp life time	50000 h
------------------------	---------

Capabilities

Dimmable	Yes
----------	-----

Certificates & Standards

Type of protection	IP20
--------------------	------

LOGISTICAL DATA

Temperature range at storage	-40...+80 °C
------------------------------	--------------

DOWNLOAD DATA

Photometric and lighting design files		Document name
	IES file (IES)	LM SPOT 111-4300-840-40D

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075149045	Folding box 1	116 mm x 116 mm x 72 mm	435.00 g	0.97 dm ³
4058075149052	Shipping box 10	600 mm x 247 mm x 95 mm	4829.00 g	14.08 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.