

# PRODUCT DATASHEET

## LED Performance Surface Mount Downlight 9 W 36 ° 3000 K White

LED PERFORMANCE SURFACE MOUNT DOWNLIGHT | LED downlights for ceiling surface mounting



### Areas of application

- Shops, supermarkets
- Public areas
- Corridors

### Product benefits

- High power COB LED provides high lumen output in compact housing
- Low flicker light thanks to special electronic control gear
- Good color rendering for the best product presentation

### Product features

- Available in two housing colors
- Available with color temperature: 3,000 K, 4,000 K
- Color rendering index  $R_a$ : > 90
- Power factor: > 0.9
- Initial color consistency: < 5 SDCM
- Lifetime (L70/B50): up to 30,000 h
- Type of protection: IP20
- CCC marked, CB test certificate



TECHNICAL DATA

Electrical data


|                           |                     |
|---------------------------|---------------------|
| Nominal wattage           | 9.00 W              |
| Nominal voltage           | 220...240 V         |
| Mains frequency           | 50...60 Hz          |
| Power factor $\lambda$    | 0.90                |
| Total harmonic distortion | < 20 %              |
| Protection class          | II                  |
| Operating mode            | External LED driver |

Photometrical data

|                                      |            |
|--------------------------------------|------------|
| Luminous flux                        | 670 lm     |
| Luminous efficacy                    | 74 lm/W    |
| Color temperature                    | 3000 K     |
| Light color (designation)            | Warm White |
| Color rendering index Ra             | 90         |
| Standard deviation of color matching | ≤5 sdcn    |
| Beam angle                           | 36 °       |

Dimensions & Weight

|                |           |
|----------------|-----------|
| Diameter       | 100.00 mm |
| Height         | 100.00 mm |
| Product weight | 445.00 g  |
| Cable length   | 110 mm    |



Materials & Colors

|               |          |
|---------------|----------|
| Product color | White    |
| Housing color | White    |
| Body material | Aluminum |

|                 |        |
|-----------------|--------|
| Mercury content | 0.0 mg |
|-----------------|--------|

### Application & Mounting

|                              |               |
|------------------------------|---------------|
| Ambient temperature range    | -20...+40 °C  |
| Temperature range at storage | -20...+70 °C  |
| Type of connection           | Cable, 2-pole |
| Type of protection           | IP20          |
| Dimmable                     | No            |
| Mounting type                | Surface       |
| Mounting location            | Ceiling       |
| Application environment      | Indoor        |
| Replaceable light source     | No            |

### Lifespan

|                            |                       |
|----------------------------|-----------------------|
| Lifespan L70/B50 at 25 °C  | 30000 h <sup>1)</sup> |
| Number of switching cycles | 30000                 |

<sup>1)</sup> t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

### Certificates & Standards

|                                  |                 |
|----------------------------------|-----------------|
| Replaceable light source (EPREL) | Not replaceable |
|----------------------------------|-----------------|

### DOWNLOAD DATA

| Photometric and lighting design files                                              |                | Document name            |
|------------------------------------------------------------------------------------|----------------|--------------------------|
|  | IES file (IES) | LDPFM SURF DL 9W/930 36D |

### LOGISTICAL DATA

| Product code  | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume                |
|---------------|------------------------------|--------------------------------------|--------------|-----------------------|
| 4058075333215 | Folding box<br>1             | 106 mm x 106 mm x 105 mm             | 493.00 g     | 1.18 dm <sup>3</sup>  |
| 4058075333222 | Shipping box<br>24           | 445 mm x 340 mm x 230 mm             | 12642.00 g   | 34.80 dm <sup>3</sup> |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

**DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.