

# PRODUCT DATASHEET

## Submarine Integrated Slim Value 1.2M 18W 4000K

SUBMARINE® Integrated Slim Value | Flat and slim dampproof luminaires with integrated LED module

---

### Areas of application

- Basements, garages, warehouses



---

### Product benefits

- Easy installation, no tools required for connection
- Impressive for its low-profile design

---

### Product features

- Damp-proof luminaires
- Dust-protected and jet-proof (IP65)
- Extremely low profile
- Not dimmable



## TECHNICAL DATA

### Electrical data

|   |             |
|---|-------------|
| Nominal wattage   | 18.00 W     |
| Nominal voltage   | 220...240 V |
| Mains frequency   | 50...60 Hz  |
| Nominal current   | 170.000 mA  |
| Max. number of luminaires per miniature circuit breaker B16 | 46          |
| Max. number of luminaires per miniature circuit breaker C16 | 59          |
| Power factor $\lambda$                                      | > 0.5       |
| Total harmonic distortion                                   | < 20 %      |
| Protection class  | II          |

### Photometrical data

|  |                      |
|--|----------------------|
| Luminous flux                                  | 1600 lm              |
| Total luminous flux of contained light sources | 1900 lm              |
| Luminous efficacy                              | 89 lm/W              |
| Color temperature                              | 4000 K               |
| Light color (designation)                      | Cool White           |
| Color rendering index Ra                       | $\geq 80$            |
| Standard deviation of color matching           | < 5 sdc <sub>m</sub> |
| Flickering metric (Pst LM)                     | <10                  |
| Photobiological safety group acc. to EN62778   | RG0                  |
| Beam angle                                     | 120 °                |

### Dimensions & Weight

|                |            |
|----------------|------------|
| Length         | 1245.00 mm |
| Width          | 53.00 mm   |
| Height         | 35.00 mm   |
| Product weight | 299.00 g   |



SUBMARINE I SLIM VALUE 1.2M  
840

## Materials & Colors

|                 |                    |
|-----------------|--------------------|
| Product color   | White              |
| Housing color   | White              |
| Body material   | Polycarbonate (PC) |
| Cover material  | Polycarbonate (PC) |
| Mercury content | 0.0 mg             |

## Application & Mounting

|  |                         |
|--|-------------------------|
| Ambient temperature range              | -20...+35 °C            |
| Type of connection                     | Terminal, 2-Pole (L, N) |
| Type of protection                     | IP65                    |
| Protection class IK (shock resistance) | IK06                    |
| Dimmable                               | No                      |
| Mounting type                          | Surface                 |
| Mounting location                      | Ceiling / Wall          |
| Application environment                | Indoor                  |
| With light source                      | Yes                     |

## Lifespan

|                            |                       |
|----------------------------|-----------------------|
| Lifespan L70/B50 at 25 °C  | 30000 h <sup>1)</sup> |
| Number of switching cycles | 25000                 |

<sup>1)</sup> t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

## Certificates & Standards

|  |                 |
|--|-----------------|
| Standards  | CE / EAC / UKCA |
| Luminaire with limited surface temperature, "D sign" | No              |
| Replaceable light source (EPREL)                     | Not replaceable |

## Additional product data

|                       |       |
|-----------------------|-------|
| Number of illuminants | empty |
|-----------------------|-------|





## EQUIPMENT / ACCESSORIES

– Complete mounting and connecting accessories included

## Safety advice

- All electrical connections must be made by a qualified person.
- Caution, risk of electric shock.

## DOWNLOAD DATA

|  | Documents and certificates             | Document name                           |
|--|--|---|
|  | User instruction / safety instructions | SUBMARINE INTEGRATED SLIM               |
|  | Legal information                      | Legal insert B-not dimmable             |
|  | Declarations of conformity             | CE Declaration SubMARINE LED Slim Value |
|  | Declarations of conformity UKCA        | Fixed LUM                               |

## LOGISTICAL DATA

| Product code  | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume                |
|---------------|------------------------------|--------------------------------------|--------------|-----------------------|
| 4058075266414 | Folding box<br>1             | 42 mm x 58 mm x 1,232 mm             | 318.00 g     | 3.00 dm <sup>3</sup>  |
| 4058075266421 | Shipping box<br>20           | 1,280 mm x 249 mm x 225 mm           | 7203.00 g    | 71.71 dm <sup>3</sup> |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.