

PRODUCT DATASHEET ENDURA Style Cylinder Wall Sensor 6W

ENDURA® STYLE CYLINDER | Stainless steel wall luminaires and bollards with indirect illumination



Areas of application

- Outdoor use (IP44)
- Building facades
- Gardens, balconies and other outdoor areas
- Pathway lighting
- Driveways

Product benefits

- Energy-efficient thanks to LED technology
- Easy and quick installation
- Long-term energy and cost savings (sensor version)

Product features

- Bright and functional outdoor LED luminaires
- Housing made of Polycarbonate covered with stainless steel
- Available as wall, ceiling and bollard luminares



TECHNICAL DATA

Electrical data


Nominal wattage	6.00 W		
Nominal voltage	220240 V		
Mains frequency	5060 Hz		
Nominal current	40.000 mA		
Max. number of luminaires per miniature circuit breaker B16	320		
Max. number of luminaires per miniature circuit breaker C16	320		
Power factor λ	> 0.5		
Total harmonic distortion	< 120 %		
Protection class	II		
Operating mode	Mains voltage		

Photometrical data

Luminous flux	360 lm	
Total luminous flux of contained light sources	660 lm	
Luminous efficacy	60 lm/W	
Color temperature	3000 K	
Light color (designation)	Warm White	
Color rendering index Ra	> 80	
Standard deviation of color matching	< 6 sdcm	
Flickering metric (Pst LM)	-	
Stroboscope effect metric (SVM)		
Photobiological safety group acc. to EN62778	RG0	
UGR	< 25	

Dimensions & Weight

Diameter	102,0 mm
Length	150.00 mm
Width	101.00 mm
Height	137.00 mm
Product weight	480.00 g



PG ENDURA STYLE Cylinder Wall Sensor MiPRC

Materials & Colors

Product color	Steel
Housing color	Steel
Body material	Stainless steel
Cover material	Polycarbonate (PC)
Mercury content	0.0 mg

Application & Mounting

Ambient temperature range	-20+40 °C	
Temperature range at storage	-20+85 °C	
Type of connection	Screw terminal	
Type of protection	IP44	
Dimmable	No	
Mounting type	Surface	
Mounting location	Wall	
Application environment	Outdoor	
With light source	Yes	
Replaceable light source	No	

Lifespan

Lifespan L70/B50 at 25 °C	40000 h ¹⁾
Number of switching cycles	15000

¹⁾ t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

Sensor

Type of sensor	Motion / Light
Sensor controlled switching time	2 s6 min

Detection range of motion sensor	9 m
Detection threshold of daylight sensor	502000 lx

Certificates & Standards

Standards	CE / EAC / UKCA
Luminaire with limited surface temperature, "D sign"	No
Replaceable light source (EPREL)	Not replaceable

Additional product data

Number of illuminants empty	Number of illuminants	empty
-----------------------------	-----------------------	-------

EQUIPMENT / ACCESSORIES

- Complete mounting and connecting accessories included

Safety advice

- All electrical connections must be made by a qualified person.
- Caution, risk of electric shock.

DOWNLOAD DATA

	Documents and certificates	Document name	
PDF	User instruction / safety instructions	ENDURA STYLE CYLINDER	
PDF	Legal information	Legal insert	
PDF	Legal information	Informationstext 18 Abs 4 ElektroG	
PDF	Declarations of conformity	CE Declaration Endura Style Cylinder	
PDF	Declarations of conformity UKCA	Fixed LUM	

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075205352	Folding box 1	124 mm x 154 mm x 166 mm	520.00 g	3.17 dm ³

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075205369	Shipping box 6	380 mm x 175 mm x 320 mm	3351.00 g	21.28 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.