

# PRODUCT DATASHEET ENDURA Classic Lantern Cylinder E27 Black

ENDURA® CLASSIC LANTERN CYLINDER | Wall luminaire, cylindrical shaped with glass diffuser



## Areas of application

- Entrance lighting
- Patios, balconies

## Product benefits

- High flexibility in the choice of the light source thanks to E27 socket
- Easy and quick installation

#### Product features

- Diffuser made of frosted glass
- Die-cast aluminum housing
- Type of protection: IP43




## **TECHNICAL DATA**

## Electrical data

| Nominal voltage  | 220240 V      |
|------------------|---------------|
| Mains frequency  | 5060 Hz       |
| Protection class | 1             |
| Operating mode   | Mains voltage |

# Dimensions & Weight

| Diameter       | 118.0 mm  |
|----------------|-----------|
| Length         | 210.00 mm |
| Width          | 118.00 mm |
| Height         | 212.00 mm |
| Product weight | 1200.00 g |



## Materials & Colors

| Product color   | Black    |
|-----------------|----------|
| Housing color   | Black    |
| Body material   | Aluminum |
| Cover material  | Glass    |
| Mercury content | 0.0 mg   |

# **Application & Mounting**

| Ambient temperature range    | -20+40 °C      |  |
|------------------------------|----------------|--|
| Temperature range at storage | -20+40 °C      |  |
| Type of connection           | Screw terminal |  |
| Type of protection           | IP43           |  |

| Dimmable                 | No      |
|--------------------------|---------|
| Mounting type            | Surface |
| Mounting location        | Wall    |
| Application environment  | Outdoor |
| With light source        | No      |
| Replaceable light source | No      |
| Holder designation       | E27     |

## Certificates & Standards

| Standards  | CE / EAC / UKCA |
|--|-----------------|
| Luminaire with limited surface temperature, "D sign" | No              |

## Additional product data

| Product remark        | Maximum bulb wattage: 60 W |
|-----------------------|----------------------------|
| Number of illuminants | 1                          |

## **EQUIPMENT / ACCESSORIES**

- Complete mounting and connecting accessories included
- No light sources included

## Safety advice

- All electrical connections must be made by a qualified person.
- Caution, risk of electric shock.
- Product in protection class I. All electrically conductive, metallic housing parts that can absorb voltage during operation or during maintenance in the event of a fault must be continuously connected to the protective earthing conductor.

#### DOWNLOAD DATA

|     | Documents and certificates             | Document name                   |
|-----|--|---------------------------------|
| POF | User instruction / safety instructions | ENDURA CLASSIC LANTERN CYLINDER |
| PDF | Legal information                      | Legal insert I-Outdoor          |
| PDF | Declarations of conformity             | ENDURA CLASSIC LANTERN CYL      |
| PDF | Declarations of conformity UKCA        | Fixed LUM without EMC           |
|     |  |                                 |

#### LOGISTICAL DATA

| Product code  | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume                |
|---------------|------------------------------|--------------------------------------|--------------|-----------------------|
| 4058075392663 | Folding box                  | 242 mm x 152 mm x 243 mm             | 1375.00 g    | 8.94 dm <sup>3</sup>  |
| 4058075392670 | Shipping box<br>4            | 506 mm x 324 mm x 273 mm             | 6250.00 g    | 44.76 dm <sup>3</sup> |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

Black