

# PRODUCT DATASHEET ENDURA Classic Lantern Square S E27

ENDURA® Classic Lantern | Classic, square-shaped lantern



## Areas of application

- Only for specially protected outdoor areas
- Suitable for outdoor applications by luminaire mounting with lamp holder facing downwards
- Entrance lighting
- Patios, balconies

#### **Product benefits**

- High flexibility in the choice of the light source thanks to E27 socket
- Easy and quick installation

# **Product features**

- Die-cast aluminum housing
- Diffuser made of clear glass
- Type of protection: IP23



# **TECHNICAL DATA**

## Electrical data

| Nominal voltage   | 220240 V |
|---|----------|
| Mains frequency   | 5060 Hz  |
| Max. number of luminaires per miniature circuit breaker C10 | -        |
| Protection class  | T .      |

# Photometrical data

| Flickering metric (Pst LM)      | - |
|---------------------------------|---|
| Stroboscope effect metric (SVM) | - |

# Dimensions & Weight

| Length         | 105.00 mm |
|----------------|-----------|
| Width          | 150.00 mm |
| Height         | 225.00 mm |
| Product weight | 685.00 g  |



# Materials & Colors

| Product color   | Black    |
|-----------------|----------|
| Housing color   | Black    |
| Body material   | Aluminum |
| Mercury content | 0.0 mg   |

# **Application & Mounting**

| Ambient temperature range | -20+40 °C       |
|---------------------------|-----------------|
| Type of connection        | Terminal, 3-pin |

| Type of protection       | IP43    |
|--------------------------|---------|
| Dimmable                 | No      |
| Mounting type            | Surface |
| Mounting location        | Wall    |
| Application environment  | Outdoor |
| With light source        | No      |
| Replaceable light source | No      |
| Holder designation       | E27     |

#### Certificates & Standards

| Standards  | CE / EAC / UKCA |
|--|-----------------|
| Luminaire with limited surface temperature, "D sign" | No              |

# Additional product data

| Product remark        | Maximum bulb wattage: 60 W |
|-----------------------|----------------------------|
| Number of illuminants | 1                          |

## **EQUIPMENT / ACCESSORIES**

- Complete mounting and connecting accessories included
- No light sources included

# Safety advice

- All electrical connections must be made by a qualified person.
- Caution, risk of electric shock.
- Product in protection class I. All electrically conductive, metallic housing parts that can absorb voltage during operation or during maintenance in the event of a fault must be continuously connected to the protective earthing conductor.

# DOWNLOAD DATA

|     | Documents and certificates Document name                                 |                        |
|-----|--|------------------------|
|     |  | ENDURA CLASSIC LANTERN |
|     |  | Legal insert I-Outdoor |
| PDF | Declarations of conformity  CE Declaration Endura Classic Lantern Square |                        |

|     | Documents and certificates      | Document name         |
|-----|---------------------------------|-----------------------|
| PDF | Declarations of conformity UKCA | Fixed LUM without EMC |

# LOGISTICAL DATA

| Product code  | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume                |
|---------------|------------------------------|--------------------------------------|--------------|-----------------------|
| 4058075206625 | Folding box<br>1             | 131 mm x 171 mm x 242 mm             | 740.00 g     | 5.42 dm <sup>3</sup>  |
| 4058075206632 | Shipping box                 | 408 mm x 357 mm x 262 mm             | 4793.00 g    | 38.16 dm <sup>3</sup> |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

# **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.