

# PRODUCT DATASHEET LINEAR SLOT VALUE 2 ft BL Direct Indirect Light Wall

LINEAR SLOT VALUE | Architectural Linear Slot with selectable CCT



## Areas of application

- Offices
- Lobbies
- Waiting rooms
- Hospitality
- Retail



## Product features

- Selectable CCTs: 3000/4000/5000K
- Direct or Direct/Indirect
- Accessories available for suspended, surface or recessed mounting are available
- Linkable
- Sleek and modern design
- Two different finishes
- CRI > 80

#### **TECHNICAL DATA**

#### Electrical data

Nominal wattage	24.00 W
Nominal voltage	120347 V

#### Photometrical data

Luminous flux	2400 lm
Luminous efficacy	100 lm/W
Color temperature	3000 4000 K
Color rendering index Ra	> 80

# Dimensions & Weight

Length	660.00 mm
Width	310.00 mm
Height	255.00 mm
Product weight	1600.00 g

# Materials & Colors

Product color	Black
Housing color	Black
Body material	Aluminum
Mercury content	0.0 mg

## **Application & Mounting**

Dimmable	Yes
Type of dimming	0-10V
Mounting type	Surface
Application environment	Indoor
Replaceable light source	No

## Certificates & Standards

|--|

# Additional product data

NAED 63730
------------

# **EQUIPMENT / ACCESSORIES**

- Suspended Mount Kit available with all SKUs aside wall mount version
- Wall Mount Kit available for all wall mounting version only

## Safety advice

- Connect up to 700W

# DOWNLOAD DATA

Photometric and lighting design files	Document name
IES file (IES)	24W 2ft linear slot 1A, 120-347V and 0-10V dimmable IES FILES
IES file (IES)	Value Class CCT Selectable Linear Slot IES FILES

#### LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
0046135637308	Folding box 1	640 mm x 95 mm x 116 mm	1958.00 g	7.05 dm <sup>3</sup>
4099854167027	Shipping box 6	660 mm x 310 mm x 255 mm	12316.00 g	52.17 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

# **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.