

# PRODUCT DATASHEET LINEAR SLOT VALUE 4 ft BL Direct Indirect Light Wall with OTi Driver

LINEAR SLOT VALUE | Architectural Linear Slot with selectable CCT

## Areas of application

- Offices
- Lobbies
- Waiting rooms
- Hospitality
- Retail

#### **Product features**

- Selectable CCTs: 3000/4000/5000K
- Direct or Direct/Indirect
- Accessories available for suspended, surface or recessed mounting are available
- Linkable
- Sleek and modern design
- Two different finishes
- CRI > 80

#### **TECHNICAL DATA**

### Electrical data

Nominal wattage	48.00 W
Nominal voltage	120277 V

### Photometrical data

Luminous flux	4800 lm
Luminous efficacy	100 lm/W
Color temperature	3000 4000 K
Color rendering index Ra	> 80

# Dimensions & Weight

Length	1212.00 mm
Width	57.00 mm
Height	76.00 mm
Product weight	2660.00 g

# Materials & Colors

Product color	Black
Housing color	Black
Body material	Aluminum
Mercury content	0.0 mg

## **Application & Mounting**

Dimmable	Yes
Type of dimming	0-10V
Mounting type	Surface
Replaceable light source	No

## Certificates & Standards

# Additional product data

NAED	67043
	<u> </u>

# **EQUIPMENT / ACCESSORIES**

- Suspended Mount Kit available with all SKUs aside wall mount version
- Wall Mount Kit available for all wall mounting version only

## Safety advice

- Connect up to 700W

### LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
0046135670435	Folding box 1	1,250 mm x 95 mm x 116 mm	3012.00 g	13.78 dm³
4099854659607	Shipping box	1,270 mm x 310 mm x 255 mm	18761.00 g	100.39 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.