



PRODUCT DATASHEET

LINEAR SLOT VALUE 4 ft BL Direct Indirect Light Wall with OTi Driver and Lutron Sensor

LINEAR SLOT VALUE | Architectural Linear Slot with selectable CCT

Areas of application

- Offices
- Lobbies
- Waiting rooms
- Hospitality
- Retail

Product features

- Selectable CCTs: 3000/4000/5000K
- Direct or Direct/Indirect
- Accessories available for suspended, surface or recessed mounting are available
- Linkable
- Sleek and modern design
- Two different finishes
- CRI > 80

TECHNICAL DATA

Electrical data

Nominal wattage	48.00 W
Nominal voltage	120...277 V

Photometrical data

Luminous flux	4800 lm
Luminous efficacy	100 lm/W
Color temperature	3000 ... 4000 K
Color rendering index Ra	> 80

Dimensions & Weight

Length	1212.85 mm
Width	101.60 mm
Height	88.90 mm
Product weight	2660.00 g

Materials & Colors

Product color	Black
Housing color	Black
Body material	Aluminum
Mercury content	0.0 mg

Application & Mounting

Dimmable	Yes
Type of dimming	0-10V
Mounting type	Surface
Replaceable light source	No

Certificates & Standards

Replaceable light source (EPREL)	Not replaceable
----------------------------------	-----------------

Additional product data

NAED	67062
------	-------

EQUIPMENT / ACCESSORIES

- Suspended Mount Kit - available with all SKUs aside wall mount version
- Wall Mount Kit - available for all wall mounting version only

Safety advice

- Connect up to 700W

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854663260	Shipping box 1	1,327 mm x 133 mm x 127 mm	3431.00 g	22.48 dm³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.