



LEDVANCE

# PRODUCT DATASHEET

## EXIT V THS WH R SD

EXIT SIGNS SELF DIAGNOSTIC | LEDVANCE LED Exit Signs and Exit Combo Signs with self diagnostic and remote capable options



VALUE  
CLASS

### Areas of application

- Emergency illumination of escape routes
- Antipanic lighting
- Offices, education, public buildings

### Product features

- Slim profile, lightweight, easy to install exit sign that replaces traditional incandescent and fluorescent exit signs
- Bright, energy-efficient LEDs provide energy savings up to 97%
- Injection-molded thermoplastic housing
- Universal mounting
- 6500K color temperature
- CRI > 80
- Offered in watts up to 3.2W
- Optional self-diagnostic and remote capable
- Both Red and Green letters shipped in exit box (running man is green only)

TECHNICAL DATA

Electrical data

Nominal wattage	2.80 W
Nominal voltage	120...277 V

Photometrical data

Luminous flux	200 lm
Luminous efficacy	71 lm/W
Color temperature	6500 K
Color rendering index Ra	80

Dimensions & Weight

Length	496.00 mm
Width	56.00 mm
Height	202.00 mm
Product weight	1500.00 g

Materials & Colors

Product color	White
Housing color	White
Mercury content	0.0 mg

Application & Mounting

Dimmable	No
Mounting type	Surface
Replaceable light source	No


Certificates & Standards

Replaceable light source (EPREL)	Not replaceable
----------------------------------	-----------------

Additional product data

NAED	66069
------	-------

DOWNLOAD DATA

Photometric and lighting design files		Document name
	IES file (IES)	VALUE CLASS EXIT AND EMERGENCY

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
0046135660696	Folding box 1	495 mm x 215 mm x 125 mm	1685.00 g	13.30 dm³
4099854335020	Shipping box 6	505 mm x 445 mm x 395 mm	10515.00 g	88.77 dm³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.