

PRODUCT DATASHEET EXIT V THR WH R SD

EXIT SIGNS SELF DIAGNOSTIC | LEDVANCE LED Exit Signs and Exit Combo Signs with self diagnostic and remote capable options

Areas of application

- Emergency illumination of escape routes
- Antipanic lighting
- Offices, education, public buildings





Product features

- Slim profile, lightweight, easy to install exit sign that replaces traditional incandescent and fluorescent exit signs
- Bright, energy-efficient LEDs provide energy savings up to 97%
- Injection-molded thermoplastic housing
- Universal mounting
- 6500K color temperature
- CRI > 80
- Offered in watts up to 3.2W
- Optional self-diagnostic and remote capable
- Both Red and Green letters shipped in exit box (running man is green only)

TECHNICAL DATA

Electrical data

Nominal wattage	2.00 W
Nominal voltage	120277 V

Photometrical data

Luminous flux	200 lm
Luminous efficacy	100 lm/W
Color temperature	6500 K
Color rendering index Ra	80

Dimensions & Weight

Length	418.00 mm
Width	52.00 mm
Height	184.00 mm
Product weight	900.00 g

Materials & Colors

Product color	White
Housing color	White
Mercury content	0.0 mg

Application & Mounting

Dimmable	No
Mounting type	Surface
Replaceable light source	No

Certificates & Standards

Additional product data

NAED 66070

DOWNLOAD DATA

Photometric and lighting design files Document name	
IES file (IES)	VALUE CLASS EXIT AND EMERGENCY

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
0046135660702	Folding box 1	430 mm x 196 mm x 65 mm	1058.00 g	5.48 dm ³
4099854335037	Shipping box 6	445 mm x 405 mm x 205 mm	6706.00 g	36.95 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.