

PRODUCT DATASHEET EXIT V WH SD

EXIT SIGNS SELF DIAGNOSTIC | LEDVANCE LED Exit Signs and Exit Combo Signs with self diagnostic and remote capable options



Areas of application

- Emergency illumination of escape routes
- Antipanic lighting
- Offices, education, public buildings

VALUE CLASS

Product features

- Slim profile, lightweight, easy to install exit sign that replaces traditional incandescent and fluorescent exit signs
- Bright, energy-efficient LEDs provide energy savings up to 97%
- Injection-molded thermoplastic housing
- Universal mounting
- 6500K color temperature
- CRI > 80
- Offered in watts up to 3.2W
- Optional self-diagnostic and remote capable
- Both Red and Green letters shipped in exit box (running man is green only)

TECHNICAL DATA

Electrical data

Nominal wattage	2.00 W
Nominal voltage	120347 V

Photometrical data

Luminous flux	6 lm
Luminous efficacy	3 lm/W
Color temperature	6500 K
Color rendering index Ra	80

Dimensions & Weight

Length	345.00 mm
Width	50.00 mm
Height	230.00 mm
Product weight	1700.00 g

Materials & Colors

Product color	White
Housing color	White
Mercury content	0.0 mg

Application & Mounting

Dimmable	No
Mounting type	Surface
Replaceable light source	No

Certificates & Standards

Replaceable light source (EPREL) Not replaceable

Additional product data

NAED 66073

DOWNLOAD DATA

Photometric and lighting design files	Document name
IES file (IES)	VALUE CLASS EXIT AND EMERGENCY

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
0046135660733	Folding box 1	358 mm x 241 mm x 70 mm	1898.00 g	6.04 dm ³
4099854335068	Shipping box 6	435 mm x 370 mm x 265 mm	11793.00 g	42.65 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.