

PRODUCT DATASHEET

EML V THS WH R SD

EMERGENCY LIGHTS SELF DIAGNOSTIC | LEDVANCE LED Emergency Lights with self diagnostic and remote capable options



Product features

- Slim profile, lightweight, easy to install emergency light that replaces traditional incandescent and fluorescent emergency lights
- Bright, energy-efficient LEDs provide energy savings up to 97%
- Offered in watts up to 2W
- Surface mounting
- 6500K color temperature
- CRI > 80
- Optional self-diagnostic and remote capable

TECHNICAL DATA

Electrical data

Nominal wattage	1.50 W
Nominal voltage	120...277 V

Photometrical data

Luminous flux	160 lm
Luminous efficacy	107 lm/W
Color temperature	6500 K
Color rendering index Ra	80

Dimensions & Weight

Length	307.00 mm
Width	98.00 mm
Height	114.00 mm
Product weight	650.00 g

Materials & Colors

Product color	White
Housing color	White
Mercury content	0.0 mg

Application & Mounting

Dimmable	No
Mounting type	Surface
Replaceable light source	No


Certificates & Standards


Replaceable light source (EPREL)	Not replaceable
----------------------------------	-----------------

Additional product data

NAED	66074
------	-------

DOWNLOAD DATA

Test		Document name	
	Extended installation guide	EXIT & EMERGENCY LIGHT	

Photometric and lighting design files		Document name
	IES file (IES)	VALUE CLASS EXIT AND EMERGENCY

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
0046135660740	Folding box 1	320 mm x 131 mm x 110 mm	808.00 g	4.61 dm³
4099854335075	Shipping box 6	410 mm x 330 mm x 240 mm	5207.00 g	32.47 dm³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.