

PRODUCT DATASHEET SATURN RING CCT SELECT 120V

SYLVANIA Saturn Ring CCT Selectable | SYLVANIA Saturn Ring luminaire with selectable CCT



Areas of application

- Indoor applications
- Home offices & study rooms
- Bedrooms & living rooms
- Entryways & foyers
- Nurseries & children's rooms

Product features

- Selectable CCTs: 2700/3000/3500/4000/5000K
- 0-10V phase-cut dimmable
- Sensor and integrated emergency battery backup available
- Easy installation no additional hardware needed
- Lifetime (L70): up to 50,000 h
- No warm up time, instant on with full light and consistent lamp to lamp color
- Damp rated, indoor

TECHNICAL DATA

Electrical data

Nominal wattage	15.00 W
Nominal voltage	120 V

Photometrical data

Luminous flux	1050 lm
Luminous efficacy	70 lm/W
Color temperature	2700 5000 K
Color rendering index Ra	90

Dimensions & Weight

Diameter	304.80 mm
Height	85.09 mm
Product weight	530.00 g

Materials & Colors

Product color	White
Housing color	White
Body material	Polycarbonate (PC)
Mercury content	0.0 mg

Application & Mounting

Dimmable	Yes
Type of dimming	PHASE CUT
Mounting type	Surface
Application environment	Indoor
Replaceable light source	No

Additional product data

NAED 65575	
------------	--

EQUIPMENT / ACCESSORIES

- Mounting screws and mounting brackets included

Safety advice

- cETLus, RoHS, ENERGY STAR
- For indoor use only; not suitable for outdoor or wet locations
- All electrical connections must be made by a qualified person.

- Caution, risk of electric shock.

DOWNLOAD DATA

Photometric and lighting design files Document name	
IES files (IES, additional)	Performance Class Puff Series .ies

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
0046135655753	Folding box 1	98 mm x 329 mm x 330 mm	797.00 g	10.64 dm ³
4058118200016	Shipping box 4	415 mm x 342 mm x 345 mm	4036.00 g	48.97 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.