

PRODUCT DATASHEET

SATURN RING CCT SELECT 120-277V

SENSOR EMBB

SYLVANIA Saturn Ring CCT Selectable | SYLVANIA Saturn Ring luminaire with selectable CCT



Areas of application

- Indoor applications
- Home offices & study rooms
- Bedrooms & living rooms
- Entryways & foyers
- Nurseries & children's rooms

Product features

- Selectable CCTs: 2700/3000/3500/4000/5000K
- 0-10V phase-cut dimmable
- Sensor and integrated emergency battery backup available
- Easy installation – no additional hardware needed
- Lifetime (L70): up to 50,000 h
- No warm up time, instant on with full light and consistent lamp to lamp color
- Damp rated, indoor

TECHNICAL DATA

Electrical data

Nominal wattage	24.00 W
Nominal voltage	120...277 V

Photometrical data

Luminous flux	1700 lm
Luminous efficacy	75 lm/W
Color temperature	2700 ... 5000 K
Color rendering index Ra	90

Dimensions & Weight

Diameter	406.40 mm
Height	85.09 mm
Product weight	1100.00 g

Materials & Colors

Product color	White
Housing color	White
Body material	Polycarbonate (PC)
Cover material	Polycarbonate (PC)
Mercury content	0.0 mg

Application & Mounting

Dimmable	Yes
Type of dimming	0-10V
Mounting type	Surface
Application environment	Indoor
Replaceable light source	No

Certificates & Standards

Replaceable light source (EPREL)	Not replaceable
----------------------------------	-----------------

Additional product data

NAED	65577
------	-------

EQUIPMENT / ACCESSORIES

– Mounting screws and mounting brackets included

Safety advice

- cETLus, RoHS, ENERGY STAR
- For indoor use only; not suitable for outdoor or wet locations
- All electrical connections must be made by a qualified person.
- Caution, risk of electric shock.

DOWNLOAD DATA

Photometric and lighting design files		Document name
	IES files (IES, additional)	Flush Mount LM79s Zip
	IES files (IES, additional)	Performance Class Puff Series .ies

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
0046135655777	Folding box 1	106 mm x 427 mm x 428 mm	1394.00 g	19.37 dm ³
4058118200030	Shipping box 4	445 mm x 445 mm x 455 mm	6738.00 g	90.10 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.