

PRODUCT DATASHEET LED DRIVER MAG BAR 3-4 BARS 120-347V 30-60W DIM

MAGNETIC RETROFIT BAR KITS | Magnetic Retrofit Bar Kit can replace fluorescent lamps in a variety of existing fixtures

Areas of application

- Offices
- Education
- Retail

Product features

- Drivers have 12V Aux to work with sensors
- Frosted plastic lens
- Dimmable down to 20 % with 0-10V driver
- 80 CRI standard, with 90 CRI option
- Selectable CCT: 3500/4000/5000K
- Selectable wattage and lumen outputs
- 120-347V
- 90% power factor
- Beam angle: 120° with frosted plastic optics

TECHNICAL DATA

Electrical data

Nominal wattage	60.00 W
Nominal voltage	120347 V
Mains frequency	5060 Hz
Protection class	П

Dimensions & Weight

Length	240.00 mm
Width	43.00 mm
Height	31.00 mm
Product weight	380.00 g

Materials & Colors

Mercury content	0.0 ma
Wordery Corners	0.0 mg

Application & Mounting

Type of protection	IP20
Dimmable	Yes
Type of dimming	0-10V

Additional product data

NAED	75910
------	-------

Accessories Optional

Product image	Product name	EAN	
	EMBB CM20N 8W DC	0046135610974	
	Standalone Microwave Motion Sensor Behind the lens ft 12ft 12V	0046135663666	

Safety advice

- Do not use 3-4 lamp driver to operate less than 3 magnetic bars
- Suitable for use in open / enclosed fixture but not vapor tight gasketed fixture.

DOWNLOAD DATA

	Photometric and lighting design files	Document name
ES	IES file (IES)	Magnetic Retrofit Bar Kit Driver 3-4 bars 30-60W

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854439124	Unpacked 1			
4099854425325	Shipping box 20	415 mm x 300 mm x 240 mm	8098.00 g	29.88 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.