



PRODUCT DATASHEET

PANELS LINK 1x4

PANELS LINK™ | Panel luminaire with LINK bluetooth low energy mesh networked lighting controls and optional motion and daylight sensors

Areas of application

- Offices
- Schools
- Hospitality
- Healthcare
- Commercial Areas

Product features

- Bluetooth® Low Energy Mesh and a range of up to 50 ft between the luminaires
- Ready for Plug&Play PIR daylight and motion sensor for additional energy savings
- Convenient-control via LINK™ app or mobile wireless wall-remote switch
- Up to 125 LPW
- CRI > 80
- Backlit technology that offers even lighting distribution without shadowing
- DLC Premium listed to maximize rebate opportunities
- Optional field installable emergency battery backup accessories are available
- Scene & Group Control: App-based presets, flexible wireless zoning
- UL1376 L3: Gateway-free; secure QR zone control via LINK™ app

TECHNICAL DATA

Electrical data

Nominal wattage	30.00 W
Nominal voltage	120...277 V

Photometrical data

Luminous flux	3750 lm
Luminous efficacy	125 lm/W
Color temperature	3000 ... 5000 K
Color rendering index Ra	80
Beam angle	120 °

Dimensions & Weight

Length	301.00 mm
Width	1213.00 mm
Height	53.30 mm
Product weight	2010.00 g

Materials & Colors

Product color	White
Housing color	White
Body material	Aluminum
Mercury content	0.0 mg

Application & Mounting

Type of connection	WAGO
Dimmable	Yes
Type of dimming	0-10V
Mounting type	Recessed
Application environment	Indoor
Replaceable light source	No










Certificates & Standards

Replaceable light source (EPREL)	Not replaceable
----------------------------------	-----------------


Additional product data

NAED	62562
------	-------

Accessories Optional

Product image	Product name	EAN
	LINK SENSOR PLUG PLAY	0046135657856
	MOUNT KIT SURFCACE 2x2	0046135620645
	MOUNT KIT SURFCACE 2x4	0046135620652
	MOUNT KIT SURFCACE 1x4	0046135620669
	MOUNT KIT SUSPENSION	0046135620676
	EMBB METAL BRIDGE 2x2 and 2x4	0046135616822
	EMBB METAL BRIDGE 1x4	0046135616839
	EMBB 1A 8W UNV DC	0046135608889
	LINK WIRELESS CONTROLLER 5 KEY BATTERY BLE	0046135626364

DOWNLOAD DATA

Photometric and lighting design files	Document name
 IES files (IES, additional)	LEDVANCE Link .ies + LM79s

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
0046135625626	Folding box 1	1,230 mm x 312 mm x 49 mm	2268.00 g	18.80 dm ³
4058075768932	Shipping box 4	1,247 mm x 210 mm x 336 mm	9600.00 g	87.99 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.