



LEDVANCE

PRODUCT DATASHEET

LINK SENSOR CEILING PIR 12V BLE

LEDVANCE LINK™ HARDWIRED SENSOR | LEDVANCE LINK Hardwired Sensors



Product features

- Commission and configure with LEDVANCE LINK™ app
- Control using either the LEDVANCE LINK™ app or the wireless controller
- Grouping and Zoning: Wirelessly group luminaires to act in sync with each other
- Scene Control: Preset various scenes for individual or group of luminaires using the app and/or wireless/wired controllers
- QR Code for Admin/Guest control: Using the LEDVANCE LINK™ app, Admin and Guest QR codes for each zone can be generated. Allows copying the settings to another phone/tablet by scanning this QR code
- Allows setting time-based schedules and high-end and low-end trim through the LEDVANCE LINK™ app

TECHNICAL DATA

Electrical data

Nominal voltage	12...24 V
Mains frequency	50 Hz

Dimensions & Weight

Length	75.95 mm
Width	75.95 mm
Height	66.55 mm
Product weight	87.2 g

Additional product data

NAED	62633
------	-------

Capabilities

Dimmable	Yes
----------	-----

Certificates & Standards

Protection class	II
Type of protection	IP66

DOWNLOAD DATA

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
0046135626333	Folding box 1	80 mm x 80 mm x 75 mm	132.00 g	0.48 dm³
4058075777156	Shipping box 100	430 mm x 430 mm x 320 mm	13670.00 g	59.17 dm³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.