



PRODUCT DATASHEET

TROFFER LINK 1x4 UNH EMBB

TROFFER LINK™ | Troffer with built in Bluetooth Low Energy Mesh Networked Lighting Controls

Areas of application

- Offices
- Schools
- Hospitality
- Healthcare
- Commercial Areas

Product features

- Selectable CCT: 3000/3500/4000/5000K
- Built-in Bluetooth® Low Energy Mesh connectivity
- DLC listing maximizes rebate opportunities
- Optional LINK PIR sensor enables field-installable occupancy & daylight control
- Up to 125 LPW
- Optional emergency battery backup versions
- CRI > 80
- Wirelessly sync luminaires and set group/individual scenes using the LINK app

TECHNICAL DATA

Electrical data

Nominal wattage	30.00 W
Nominal voltage	120...347 V

Photometrical data

Luminous flux	1905 ... 3810 lm
Luminous efficacy	125 lm/W
Color temperature	3000 ... 5000 K
Color rendering index Ra	> 80

Dimensions & Weight

Length	1213.00 mm
Width	298.00 mm
Height	50.00 mm
Product weight	3900.00 g

Materials & Colors

Product color	White
Housing color	White
Body material	Steel
Mercury content	0.0 mg

Application & Mounting

Dimmable	Yes
Type of dimming	0-10V
Mounting type	Recessed
Application environment	Indoor
Replaceable light source	No

BATTERY

Battery size [GMS]	Others
--------------------	--------

Certificates & Standards

Replaceable light source (EPREL)	Not replaceable
----------------------------------	-----------------

Additional product data

NAED	63913
------	-------

Accessories Optional

Product image	Product name	EAN
	MOUNT KIT SURFACE 1A 1x4	10046135625906
	MOUNT KIT SURFACE 1A 2x2	10046135625913
	MOUNT KIT SURFACE 1A 2x4	10046135625920
	LINK SENSOR PLUG PLAY	0046135657856
	MOUNT KIT FLANGE 1x4	0046135604577
	MOUNT KIT FLANGE 2x2	0046135604584
	MOUNT KIT FLANGE 2x4	0046135604591
	LINK WIRELESS CONTROLLER 5 KEY BATTERY BLE	0046135626364

EQUIPMENT / ACCESSORIES

- Optional surface mount kits and flange kits

Safety advice

- Intended for recessed or surface mounting

DOWNLOAD DATA

Photometric and lighting design files		Document name
	IES file (IES)	IES files for DUAL SELECTABLE VOLUMETRIC 7B TROFFER

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854215223	Shipping box 2	1,255 mm x 315 mm x 115 mm	8904.00 g	45.47 dm³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.