

PRODUCT DATASHEET RT NIGHT RING 4" 5CCT 700LM 120V

DOWNLIGHT RETROFIT NIGHT RING | Downlight Retrofit with Night Ring technology and selectable 5 CCT



Areas of application

- Residential
- Nightlight as an orientation light or safety light for children's rooms, stairs, or bedrooms

Product features

- Integrated white trim, E26 medium base socket adapter
- Nightlight option offers a 2200K CCT and 20lms creating a calming ambient glow
- Selectable CCTs: 2700/3000/3500/4000/5000K
- Available in 120VAC
- Up to 87 LPW
- Energy savings up to 92 %
- Flicker-free dimming, phase-cut down to 10 %

TECHNICAL DATA

Electrical data

Nominal wattage	8.00 W
Nominal voltage	120 V

Photometrical data

Luminous flux	700 lm
Luminous efficacy	80 lm/W
Color temperature	2700 5000 K
Color rendering index Ra	90

Dimensions & Weight

Diameter	127.00 mm
Height	57.00 mm
Product weight	180.00 g

Materials & Colors

Product color	White
Housing color	White
Body material	Polycarbonate (PC)
Mercury content	0.0 mg

Application & Mounting

Dimmable	Yes
Type of dimming	PHASE CUT
Mounting type	Recessed
Replaceable light source	No

Certificates & Standards

Additional product data

NAED	65797

Accessories Optional

Product image	Product name EAN	
0	RT TRIM RING RT4 SM BLACK	0046135624988

Product image	Product name	EAN
0	RT TRIM RING RT4 SM COPPER	0046135624995
0	RT TRIM RING RT4 SM SATIN NICKEL	0046135625008
0	RT TRIM RING RT56 SM BLK	0046135625015
0	RT TRIM RING RT56 SM COPPER	0046135625022
0	RT TRIM RING RT56 SM SATIN NICKEL	0046135625039

Safety advice

- Suitable for damp locations.

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
0046135657979	Folding box 1	155 mm x 45 mm x 155 mm	228.00 g	1.08 dm ³
4099854264160	Shipping box 12	326 mm x 290 mm x 168 mm	2870.00 g	15.88 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.