

PRODUCT DATASHEET

RT SELECT 1AS 4" 5CCT BA LM SELECT

DOWNLIGHT RETROFIT SELECTABLE | Downlightt Retrofit with selectable 5 CCT and dual selectable models



Areas of application

- Residential
- Bedrooms
- Kitchens
- Bathrooms

Product features

- Integrated white trim, E26 medium base socket adapter
- Selectable CCTs: 2700/3000/3500/4000/5000K
- Available in 120VAC
- Up to 100 LPW
- Energy savings up to 89 %
- Flicker-free dimming, phase-cut down to 10 %
- Color trim rings available as optional accessory
- No warm-up time, instant-on with full light output

TECHNICAL DATA

Electrical data

Nominal wattage	7.00 W
Nominal voltage	120 V

Photometrical data

Luminous flux	500 ... 700 lm
Luminous efficacy	100 lm/W
Color temperature	2700 ... 5000 K
Color rendering index Ra	90

Dimensions & Weight

Diameter	128.00 mm
Height	62.00 mm
Product weight	170.00 g

Materials & Colors

Product color	White
Housing color	White
Body material	Polycarbonate (PC)
Mercury content	0.0 mg

Application & Mounting

Type of connection	WAGO
Dimmable	Yes
Type of dimming	PHASE CUT
Mounting type	Recessed
Replaceable light source	No
Holder designation	E26

Additional product data

NAED	65737
------	-------

Accessories Optional

Product image	Product name	EAN
	RT TRIM RING RT4 SM BLACK	0046135624988
	RT TRIM RING RT4 SM COPPER	0046135624995

Product image	Product name	EAN
	RT TRIM RING RT4 SM SATIN NICKEL	0046135625008
	RT TRIM RING RT56 SM BLK	0046135625015
	RT TRIM RING RT56 SM COPPER	0046135625022
	RT TRIM RING RT56 SM SATIN NICKEL	0046135625039
	RT TRIM RING RT4 BA BLK	0046135634307
	RT TRIM RING RT4 BA COPPER	0046135634314
	RT TRIM RING RT4 BA SATIN NICKEL	0046135634321
	RT TRIM RING RT56 BA BLK	0046135634338
	RT TRIM RING RT56 BA COPPER	0046135634345
	RT TRIM RING RT56 BA SATIN NICKEL	0046135634352

Safety advice

- Suitable for indoor dry, damp and wet locations.
- For use in housings that can structurally support a lamp weighing one pound.
- RT5/6 designed to install in standard 5" and 6" insulated and non-insulated housings.
- Not intended for use with emergency light luminaires or exit lights.

DOWNLOAD DATA

Photometric and lighting design files	Document name
 IES files (IES, additional)	LEDRT1A .ies ZIP

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
0046135657375	Folding box 1	137 mm x 79 mm x 142 mm	225.00 g	1.54 dm ³
10046135657372	Shipping box 4	280 mm x 165 mm x 152 mm	1052.00 g	7.02 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.