

PRODUCT DATASHEET

RT SELECT 1A 5/6" 5CCT 900LM BA

DOWNLIGHT RETROFIT SELECTABLE | Downlightt Retrofit with selectable 5 CCT and dual selectable models



Areas of application

- Residential
- Bedrooms
- Kitchens
- Bathrooms

Product features

- Integrated white trim, E26 medium base socket adapter
- Selectable CCTs: 2700/3000/3500/4000/5000K
- Available in 120VAC
- Up to 100 LPW
- Energy savings up to 89 %
- Flicker-free dimming, phase-cut down to 10 %
- Color trim rings available as optional accessory
- No warm-up time, instant-on with full light output

TECHNICAL DATA

Electrical data

Nominal wattage	10.00 W
Nominal voltage	120 V

Photometrical data

Luminous flux	900 lm
Luminous efficacy	80 lm/W
Color temperature	2700 ... 5000 K
Color rendering index Ra	90

Dimensions & Weight

Diameter	187.00 mm
Height	70.00 mm
Product weight	200.00 g

Materials & Colors

Product color	White
Housing color	White
Body material	Polycarbonate (PC)
Mercury content	0.0 mg

Application & Mounting

Dimmable	Yes
Type of dimming	PHASE CUT
Mounting type	Recessed
Replaceable light source	No

Certificates & Standards

Replaceable light source (EPREL)	Not replaceable
----------------------------------	-----------------

Additional product data

NAED	62871
------	-------

Accessories Optional

Product image	Product name	EAN
	RT TRIM RING RT4 SM BLACK	0046135624988

Product image	Product name	EAN
	RT TRIM RING RT4 SM COPPER	0046135624995
	RT TRIM RING RT4 SM SATIN NICKEL	0046135625008
	RT TRIM RING RT56 SM BLK	0046135625015
	RT TRIM RING RT56 SM COPPER	0046135625022
	RT TRIM RING RT56 SM SATIN NICKEL	0046135625039
	RT TRIM RING RT4 BA BLK	0046135634307
	RT TRIM RING RT4 BA COPPER	0046135634314
	RT TRIM RING RT4 BA SATIN NICKEL	0046135634321
	RT TRIM RING RT56 BA BLK	0046135634338
	RT TRIM RING RT56 BA COPPER	0046135634345
	RT TRIM RING RT56 BA SATIN NICKEL	0046135634352

Safety advice

- Suitable for indoor dry, damp and wet locations.
- For use in housings that can structurally support a lamp weighing one pound.
- RT5/6 designed to install in standard 5" and 6" insulated and non-insulated housings.
- Not intended for use with emergency light luminaires or exit lights.

DOWNLOAD DATA

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
0046135628719	Folding box 1	80 mm x 193 mm x 194 mm	285.00 g	3.00 dm ³
4099854011856	Shipping box 6	393 mm x 251 mm x 209 mm	1899.00 g	20.61 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.