

PRODUCT DATASHEET

LED LIGHT DISK 3000K 900LM

DOWNLIGHT LIGHT DISK KIT CCT SELECTABLE | Downlight light disk kit with selectable 5 CCT



PERFOR-
MANCE
CLASS

Areas of application

- Residential

Product features

- Lasts up to 25x longer than incandescent lamps
- Available in 120VAC
- Up to 75 LPW
- Energy savings up to 85 %
- Flicker-free dimming, phase-cut down to 10 %
- Uniform, glare free illumination distribution

TECHNICAL DATA

Electrical data

Nominal wattage	15.00 W
Nominal voltage	120 V

Photometrical data

Luminous flux	900 lm
Luminous efficacy	65 lm/W
Color temperature	3000 K
Color rendering index Ra	90

Dimensions & Weight

Diameter	190.50 mm
Height	29.00 mm
Product weight	205.00 g

Materials & Colors

Product color	White
Housing color	White
Body material	Polycarbonate (PC) Acrylonitrile butadiene styrene (ABS)
Mercury content	0.0 mg

Application & Mounting

Dimmable	Yes
Type of dimming	PHASE CUT
Mounting type	Surface
Application environment	Indoor
Replaceable light source	No
Holder designation	E26


Additional product data

NAED	62445
------	-------

Safety advice

- Suitable for indoor dry, damp and wet locations.

DOWNLOAD DATA

Photometric and lighting design files		Document name
	IES files (IES, additional)	Performance Class Light Disk

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
0046135624452	Folding box 1	197 mm x 39 mm x 197 mm	315.00 g	1.51 dm ³
10046135624459	Shipping box 4	210 mm x 165 mm x 220 mm	1521.00 g	7.62 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.