

# PRODUCT DATASHEET RT GIMBAL 5/6" 5CCT 725LM

SYLVANIA DOWNLIGHT RETROFIT GIMBAL CCT SELECTABLE | SYLVANIA Downlight Retrofit gimbal with selectable 5 CCT



## Areas of application

- Residential
- Offices
- Retail
- Education

## **Product features**

- Integrated white trim, E26 medium base socket adapter
- Selectable CCTs: 2700/3000/3500/4000/5000K
- Available in 120VAC
- Up to 90 LPW
- Energy savings up to 88 %
- $-\,$  Flicker-free dimming, phase-cut down to 10 %
- Beam angle 110°

#### **TECHNICAL DATA**

#### Electrical data

Nominal wattage	8 W
Nominal voltage	120 V

## Photometrical data

Luminous flux	725 lm
Luminous efficacy	90 lm/W
Color temperature	2700 K
Color rendering index Ra	90

# Dimensions & Weight

Diameter	182.88 mm
Length	70.87 mm
Product weight	146.00 g

#### Materials & Colors

Mercury content	0.0 mg

# **Application & Mounting**

Dimmable	Yes
Replaceable light source	No
Holder designation	E26

# Additional product data

	NAED	65120
-		

# Safety advice

- Suitable for indoor dry, damp and wet locations.
- Not intended for use with emergency light luminaires or exit lights.

# DOWNLOAD DATA

#### LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
0046135651205	Folding box 1	97 mm x 195 mm x 197 mm	273.00 g	3.69 dm <sup>3</sup>
4058118153046	Shipping box 4	401 mm x 205 mm x 211 mm	1373.00 g	17.37 dm³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.