

PRODUCT DATASHEET

RT GIMBAL 5/6" 5CCT 900LM

SYLVANIA DOWNLIGHT RETROFIT GIMBAL CCT SELECTABLE | SYLVANIA Downlight Retrofit gimbal with selectable 5 CCT



Areas of application

- Residential
- Offices
- Retail
- Education

Product features

- Integrated white trim, E26 medium base socket adapter
- Selectable CCTs: 2700/3000/3500/4000/5000K
- Available in 120VAC
- Up to 90 LPW
- Energy savings up to 88 %
- Flicker-free dimming, phase-cut down to 10 %
- Beam angle 110°

TECHNICAL DATA

Electrical data

Nominal wattage	10 W
Nominal voltage	120 V

Photometrical data

Luminous flux	900 lm
Luminous efficacy	90 lm/W
Color temperature	2700 K
Color rendering index Ra	90

Dimensions & Weight

Diameter	182.88 mm
Length	70.87 mm
Product weight	287.00 g

Materials & Colors

Mercury content	0.0 mg
-----------------	--------

Application & Mounting

Dimmable	Yes
Replaceable light source	No
Holder designation	E26

Additional product data

NAED	65121
------	-------

Safety advice

- Suitable for indoor dry, damp and wet locations.
- Not intended for use with emergency light luminaires or exit lights.

DOWNLOAD DATA

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
0046135651212	Folding box 1	97 mm x 195 mm x 197 mm	273.00 g	3.69 dm³
4058118153053	Shipping box 4	401 mm x 205 mm x 211 mm	1937.00 g	17.37 dm³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.