

PRODUCT DATASHEET RT GIMBAL 4" 5CCT 700LM

SYLVANIA DOWNLIGHT RETROFIT GIMBAL CCT SELECTABLE | SYLVANIA Downlight Retrofit gimbal with selectable 5 CCT



Areas of application

- Residential
- Offices
- Retail
- Education

Product features

- Integrated white trim, E26 medium base socket adapter
- Selectable CCTs: 2700/3000/3500/4000/5000K
- Available in 120VAC
- Up to 90 LPW
- Energy savings up to 88 %
- $-\,$ Flicker-free dimming, phase-cut down to 10 %
- Beam angle 110°

TECHNICAL DATA

Electrical data

Nominal wattage	8 W
Nominal voltage	120 V

Photometrical data

Luminous flux	700 lm
Luminous efficacy	87 lm/W
Color temperature	2700 K
Color rendering index Ra	90

Dimensions & Weight

Diameter	127.99 mm
Length	63.75 mm
Product weight	200.00 g

Materials & Colors

Mercury content	0.0 mg

Application & Mounting

Dimmable	Yes
Replaceable light source	No
Holder designation	E26

Additional product data

		NAED	65118
--	--	------	-------

Safety advice

- Suitable for indoor dry, damp and wet locations.
- Not intended for use with emergency light luminaires or exit lights.

DOWNLOAD DATA

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
0046135651182	Folding box 1	82 mm x 136 mm x 142 mm	277.00 g	1.58 dm ³
4058118153022	Shipping box 4	286 mm x 176 mm x 156 mm	1281.00 g	7.88 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

December 19, 2025, 18:57:43

RT GIMBAL 4" 5CCT 700LM