

# PRODUCT DATASHEET

## SLIM DNL 9" 5CCT 1200LM

SYLVANIA RETROFIT DOWNLIGHT SLIM CCT SELECTABLE | Retrofit downlight slim with multiple mounting options and selectable 5 CCT



---

### Areas of application

- Residential
- Hospitality
- Retail

---

### Product features

- Hybrid install with screw base and torsion springs for existing recessed cans
- Included optional mounting plate for flush hardwired mounting
- Selectable CCTs: 2700/3000/3500/4000/5000K
- Up to 71 LPW
- Energy savings up to 86 %
- Flicker-free dimming, phase-cut down to 10 %
- Available in 120VAC
- Optional dusk to dawn and PIR sensor for further energy savings

---

## TECHNICAL DATA

### Electrical data

|                 |         |
|-----------------|---------|
| Nominal wattage | 21.00 W |
| Nominal voltage | 120 V   |

### Photometrical data

|                          |                 |
|--------------------------|-----------------|
| Luminous flux            | 1500 lm         |
| Luminous efficacy        | 71 lm/W         |
| Color temperature        | 2700 ... 5000 K |
| Color rendering index Ra | 90              |

### Dimensions & Weight

|                |           |
|----------------|-----------|
| Diameter       | 300.00 mm |
| Height         | 17.78 mm  |
| Product weight | 1140.00 g |

### Materials & Colors

|               |                    |
|---------------|--------------------|
| Product color | White              |
| Housing color | White              |
| Body material | Polycarbonate (PC) |

### Application & Mounting

|                          |                  |
|--------------------------|------------------|
| Dimmable                 | Yes              |
| Type of dimming          | PHASE CUT        |
| Mounting type            | Surface/Recessed |
| Replaceable light source | No               |

### Certificates & Standards

|                                  |                 |
|----------------------------------|-----------------|
| Replaceable light source (EPREL) | Not replaceable |
|----------------------------------|-----------------|

### Additional product data

|      |       |
|------|-------|
| NAED | 62036 |
|------|-------|

---

## EQUIPMENT / ACCESSORIES

- E26 Socket and torsion springs included for recessed can
- Hardwire mounting plate

---

### Safety advice

- Suitable for wet locations.
-

– Torsion springs not recommended for 5" or 12" versions.

## DOWNLOAD DATA

| Photometric and lighting design files                                            |                             | Document name              |
|----------------------------------------------------------------------------------|-----------------------------|----------------------------|
|  | IES files (IES, additional) | Downlight Photometric Data |

## LOGISTICAL DATA

| Product code  | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume                |
|---------------|------------------------------|--------------------------------------|--------------|-----------------------|
| 0046135620362 | Folding box<br>1             | 42 mm x 304 mm x 306 mm              | 1264.00 g    | 3.91 dm <sup>3</sup>  |
| 4058118199488 | Shipping box<br>4            | 314 mm x 185 mm x 320 mm             | 5321.00 g    | 18.59 dm <sup>3</sup> |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.