

PRODUCT DATASHEET LEDSLMDNL 7" 5CCT 960LM

SYLVANIA DOWNLIGHT 7" CCT SELECTABLE | Downlight 7" with multiple mounting options and selectable 5 CCT



Areas of application

- Retail
- Offices
- Education
- Low-bay applications

Product features

- Hybrid install into existing recessed cans and junction boxes
- No warm up time, instant on with full light and consistent lamp to lamp color
- Selectable CCTs: 2700/3000/3500/4000/5000K
- Up to 80 LPW
- Energy savings up to 84 %
- Beam angle 110°
- Available in 120VAC

TECHNICAL DATA

Electrical data

Nominal wattage	12.00 W
Nominal voltage	120 V

Photometrical data

Luminous flux	960 lm
Luminous efficacy	80 lm/W
Color temperature	2700 5000 K
Color rendering index Ra	80

Dimensions & Weight

Diameter	177.80 mm
Height	12.70 mm
Product weight	440.00 g

Materials & Colors

Product color	White
Housing color	White
Body material	Aluminum Plastic

Application & Mounting

Dimmable	Yes
Type of dimming	PHASE CUT
Mounting type	Recessed
Application environment	Indoor
Replaceable light source	No
Holder designation	E26

Additional product data

NAED	65555
------	-------

Safety advice

- Suitable for wet locations.

DOWNLOAD DATA

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
0046135655555	Folding box 1	55 mm x 184 mm x 190 mm	522.00 g	1.92 dm³
4058118182466	Shipping box 4	238 mm x 195 mm x 211 mm	2303.00 g	9.79 dm³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.