

# PRODUCT DATASHEET

## LEDMD SLIM SELECT 2A 12" 5CCT 2000LM 120V

SYLVANIA MICRODISK SLIM CCT SELECTABLE | Slim Microdisk Downlight with selectable 5 CCT



### Areas of application

- Residential
- New installations or retrofit of existing installations

### Product features

- Canless recessed flush mount downlight with remote driver design for easy installation
- 1/2" height allows installation directly under joists
- Selectable CCTs: 2700/3000/3500/4000/5000K
- Flicker-free dimming, Phase-cut
- Up to 80 LPW
- Energy savings up to 92 %
- Available in 120VAC
- Beam Angle of 112° FWHM
- 90 CRI, R9>50

TECHNICAL DATA

Electrical data

Nominal wattage	27.00 W
Nominal voltage	120 V

Photometrical data

Luminous flux	2000 lm
Luminous efficacy	75 lm/W
Color temperature	2700 ... 5000 K
Color rendering index Ra	90

Dimensions & Weight

Diameter	330.00 mm
Height	23.37 mm
Product weight	820.00 g

Materials & Colors

Product color	White
Housing color	White
Body material	Aluminum Plastic
Mercury content	0.0 mg

Application & Mounting

Dimmable	Yes
Type of dimming	PHASE CUT
Mounting type	Recessed
Application environment	Indoor
Replaceable light source	No

Certificates & Standards



Replaceable light source (EPREL)	Not replaceable
----------------------------------	-----------------

Additional product data

NAED	65526
------	-------

Accessories Optional

Product image	Product name	EAN
	MD EXT CABLE 6FT WH	0046135608988
	MD EXT CABLE 10FT WH	0046135608995

Product image	Product name	EAN
	MD EXT CABLE 20FT WH	0046135609008
	SLIM MD FRAME	0046135629594
	MD FRAME T-GRID	0046135637438


## EQUIPMENT / ACCESSORIES

- Luminaire with interconnected cable to galvanized steel remote driver wiring enclosure via FT6 cable
- 3 Push-on Wire Terminals

## Safety advice

- Suitable for indoor, dry, and wet locations.
- IC Rated.
- Not intended for use with emergency light luminaires or exit lights.
- Suitable for use in closets, compliant with NFPA 70, NEC section 410.16 (A)(3) and 410.16 (C)(5).
- For use in housings that can structurally support a lamp weighing one pound.
- Max Ceiling Thickness 0.37" (9.4 mm).

## DOWNLOAD DATA

Photometric and lighting design files	Document name
 IES files (IES, additional)	Downlight Photometric Data

## LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
0046135655265	Folding box 1	50 mm x 333 mm x 333 mm	912.00 g	5.55 dm <sup>3</sup>
10046135655262	Shipping box 4	350 mm x 225 mm x 357 mm	3930.00 g	28.11 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.