

# PRODUCT DATASHEET

## LED NFC PROGRAMMABLE DRIVER 2CH 85W UNH DIM AUX

tapTronic™ NFC LED Driver Constant Current 2-Channel Output | NFC Programmable LED driver with 2 channel output



---

### Areas of application

- Wall and ceiling
- Recessed and surface-mounted ceiling luminaires
- Suspended luminaires

---

### Product features

- Field-programmable via free app
- Dim to off – dim range 1-100 %
- Constant lumen output
- Soft start
- End of life
- Thermal protection
- DC Auxiliary output
- cULus Class 2 and Class P
- The two-channel outputs are independent of each other without interference
- App is multi-lingual: English/French/Spanish/Portuguese

## TECHNICAL DATA

### Electrical data

Nominal wattage	85.00 W
Nominal voltage	120...347 V
Mains frequency	50...60 Hz

### Dimensions & Weight

Length	380.00 mm
Width	31.00 mm
Height	26.00 mm
Product weight	250.00 g

### Capabilities

Dimmable	Yes
----------	-----


### Certificates & Standards

Protection class	II
Type of protection	IP20

### Safety advice

- Always power off the driver before making any changes in programming via app.

## DOWNLOAD DATA

Test	Document name
 Extended installation guide	tapTronic 55W 2-Independent Channels

## LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
0046135758928	Unpacked 1	380 mm x 31 mm x 26 mm	250.00 g	0.31 dm <sup>3</sup>
4099854308161	Shipping box 20	400 mm x 195 mm x 190 mm	5315.00 g	14.82 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.