

PRODUCT DATASHEET

LED NCF PROGRAMMABLE DRIVER

COMPACT 40W UNV 1400mA DIM1 AUX12 F-CAN

tapTronic™ NFC LED Driver Constant Current Compact | Compact NFC programmable LED driver



Areas of application

- Pendants
- Home and décor
- Spotlights
- Downlights

Product features

- Field-programmable via free app
- Dim to off – dim range 1-100 %
- Constant lumen output
- Soft start
- End of life
- Thermal protection
- F-can and J-can
- DC Auxiliary output
- cULus Class 2 and Class P
- App is multi-lingual: English/French/Spanish/Portuguese

TECHNICAL DATA

Electrical data

Nominal wattage	40.00 W
Nominal voltage	120...277 V
Mains frequency	50...60 Hz

Dimensions & Weight

Length	129.60 mm
Width	59.00 mm
Height	27.50 mm
Product weight	250.00 g

Capabilities

Dimmable	Yes
----------	-----


Certificates & Standards

Type of protection	IP20
--------------------	------

Safety advice

- Suitable for dry and damp environments.
- Use only within an enclosure or equivalent.
- Compact drivers may get overloaded.

DOWNLOAD DATA

Test		Document name
	Extended installation guide	installation guide 100W NFC Outdoor Constant Current LED Driver

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
0046135758522	Unpacked 1	130 mm x 59 mm x 28 mm	250.00 g	0.21 dm ³
4058075792265	Shipping box 20	391 mm x 333 mm x 90 mm	5352.00 g	11.72 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.