

PRODUCT DATASHEET

ULTRA LED A19 5.5W DIM FR 3000K 1PK

SYLVANIA ULTRA A19 Lamps | Dimmable ULTRA A19 LED lamps with 80+ CRI and 15,000-hour rated life



Areas of application

- Downlights, pendant fixtures, table lamps, wall sconces
- Healthcare, hospitality, residential, retail
- Indoor and outdoor
- Suitable for rough service

Product features

- 15,000 hours lifetime (L70)
- RoHS compliant, mercury and lead free
- UV and IR free
- Reduces energy consumption up to 85 %
- Last up to 20 times longer than incandescent lamps



- No warm-up time, instant-on with full light output and stable color
- Dimmable down to 10 %
- Approved for enclosed fixtures

TECHNICAL DATA

Electrical data

Nominal wattage	5.5 W
Construction wattage	5.50 W
Nominal voltage	120 V
Claimed equiv. conventional lamp power	40 W
Operating frequency	50...60 Hz
Mains frequency	50...60 Hz

Photometrical data

Luminous flux	450 lm
Luminous efficacy	81 lm/W
Light color (designation)	Warm White
Color temperature	3000 K
Color rendering index Ra	80
Light color	830

Dimensions & Weight

Overall length	107.01 mm
Diameter	59.99 mm
Product weight	59.99 g

Temperatures & operating conditions

Ambient temperature range	-20...+45 °C
---------------------------	--------------

Additional product data

Base (standard designation)	E26
Mercury content	0.0 mg
Mercury-free	Yes
Product remark	All technical parameters apply to the entire lamp / Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value

Capabilities

Dimmable	Yes
----------	-----

Country-specific categorizations

Order reference	LED5.5A19DIMO83
-----------------	-----------------

Energy labelling regulation data acc EU 2019/2015

Light source cap-type (or other electric interface)	E26
Length	107.01 mm
Height	59.99 mm
Width	59.99 mm

Safety advice

- Suitable for damp locations.
- Not for use with emergency light fixtures or exit lights.
- -4°F and + 113°F (-20°C and +45°C)

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
0046135743986	Folding box 1	60 mm x 60 mm x 114 mm	87.00 g	0.42 dm ³
10046135743983	Shipping box 6	194 mm x 133 mm x 130 mm	619.00 g	3.36 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.