

PRODUCT DATASHEET Rough Service A19 8.5W FR 4100K 2PK

SYLVANIA Rough Service A19 Lamps | SYLVANIA Rough Service A19 is resistant to shock, vibration and impact



Areas of application

- Inspection lamps, garage door lamps, shop lights, task lights
- Indoor and outdoor

Product features

- Shatter and vibration resistant
- 11,000 hours lifetime (L70)
- Lasts up to 10 times longer than incandescent lamps
- No warm-up time, instant-on with full light output and stable color
- Approved for enclosed fixtures

TECHNICAL DATA

Electrical data

Nominal wattage	8.5 W
Construction wattage	8.50 W
Nominal voltage	120 V
Claimed equiv. conventional lamp power	60 W

Photometrical data

Luminous flux	800 lm
Luminous efficacy	94 lm/W
Color temperature	4100 K
Color rendering index Ra	80
Light color	841

Dimensions & Weight

Overall length	110.01 mm
Diameter	59.99 mm
Product weight	50.01 g

Additional product data

Base (standard designation)	E26
Mercury content	0.0 mg

Capabilities

Dimmable	No
----------	----

Country-specific categorizations

Order reference	8,5W/841 120V 6

Energy labelling regulation data acc EU 2019/2015

Light source cap-type (or other electric interface)	E26
Length	110.01 mm
Height	59.99 mm
Width	59.99 mm

Safety advice

- Not for use with emergency light fixtures or exit lights.
- Suitable for damp locations not for use where directly exposed to water.
- Not intended for use with dimmers.
- -4°F and +104°F (-20°C and +40°C)
- Suitable for use in totally enclosed fixtures

DOWNLOAD DATA

Photometric and lighting design files	Document name
IES file (IES)	LED A19, 8.5W 80CRI, 800 Lumen, 4100K IES FILES

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
0046135402128	Folding box 2	60 mm x 108 mm x 114 mm	132.00 g	0.74 dm ³
10046135402125	Shipping box 12	248 mm x 206 mm x 124 mm	986.00 g	6.33 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.