

## PRODUCT DATASHEET

### Contractor Series 10YR A19 8.5W FR 2700K 12PK

SYLVANIA Contractor Series A19 Lamps | SYLVANIA Contractor Series are rated for up to 11,000 hours



#### Areas of application

- Downlights, pendant fixtures, table lamps, wall sconces
- Healthcare, hospitality, residential, retail
- Suitable for rough service

#### Product features

- Reduces energy consumption up to 86 %
- 11,000 hours lifetime (L70)
- No warm-up time, instant-on with full light output and stable color



## TECHNICAL DATA

### Electrical data

|                                        |            |
|----------------------------------------|------------|
| Nominal wattage                        | 8.5 W      |
| Construction wattage                   | 8.50 W     |
| Nominal voltage                        | 120 V      |
| Claimed equiv. conventional lamp power | 60 W       |
| Operating frequency                    | 50...60 Hz |
| Mains frequency                        | 50...60 Hz |

### Photometrical data

|                           |            |
|---------------------------|------------|
| Luminous flux             | 800 lm     |
| Luminous efficacy         | 94 lm/W    |
| Light color (designation) | Warm White |
| Color temperature         | 2700 K     |
| Color rendering index Ra  | 80         |
| Light color               | 827        |

### Dimensions & Weight

|                |           |
|----------------|-----------|
| Overall length | 110.00 mm |
| Diameter       | 60.00 mm  |
| Product weight | 50.00 g   |

### Temperatures & operating conditions

|                           |              |
|---------------------------|--------------|
| Ambient temperature range | -20...+40 °C |
|---------------------------|--------------|

### Additional product data

|                             |                                                                                                                                                                                                                                                                                                                                              |
|-----------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Base (standard designation) | E26                                                                                                                                                                                                                                                                                                                                          |
| Mercury content             | 0.0 mg                                                                                                                                                                                                                                                                                                                                       |
| Mercury-free                | Yes                                                                                                                                                                                                                                                                                                                                          |
| Product remark              | All technical parameters apply to the entire lamp / Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value |

### Capabilities

|          |    |
|----------|----|
| Dimmable | No |
|----------|----|

## Certificates &amp; Standards

|           |                                 |
|-----------|---------------------------------|
| Standards | RoHS / CSA / FTC / FCC / cETLus |
|-----------|---------------------------------|

## Country-specific categorizations

|                 |                 |
|-----------------|-----------------|
| Order reference | 8,5W/827 120V V |
|-----------------|-----------------|

## Energy labelling regulation data acc EU 2019/2015

|                                                     |           |
|-----------------------------------------------------|-----------|
| Light source cap-type (or other electric interface) | E26       |
| Length                                              | 110.00 mm |
| Height                                              | 60.00 mm  |
| Width                                               | 60.00 mm  |

## Safety advice

- Suitable for damp locations.
- Non-dimmable.
- -4°F and +104°F (-20°C and +40°C)
- Approved for use in totally enclosed fixtures.

## LOGISTICAL DATA

| Product code   | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume               |
|----------------|------------------------------|--------------------------------------|--------------|----------------------|
| 10046135402026 | Shipping box<br>12           | 130 mm x 219 mm x 187 mm             | 899.00 g     | 5.34 dm <sup>3</sup> |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.