

PRODUCT DATASHEET TruWave® 5CCT Selectable A21 15W 2PK

SYLVANIA TruWave® 5CCT Selectable A19 Lamps | TruWave A19 lamps with natural light, 5CCT selectable , and 90+ CRI



Areas of application

- Downlights, pendant fixtures, table lamps, wall sconces
- Healthcare, hospitality, residential, retail

Product features

- Selectable CCTs: 2700/3000/3500/4000/5000K
- Controls blue wavelengths for lower glare and reduced eye strain to improve readability
- Supports an improved sleep-wake cycle
- Clean light color rendering for seeing realistic, vivid colors
- Exceptional color quality without the loss of efficacy typical of most 90+ CRI solutions
- Properly saturates red to make building spaces and flesh tones accurate and vibrant
- 25,000 hours lifetime (L70)
- CRI 90+ for exceptional color quality

TECHNICAL DATA

Electrical data

| Nominal wattage | 15 W |
|--|---------|
| Construction wattage | 15.00 W |
| Nominal voltage | 120 V |
| Claimed equiv. conventional lamp power | 100 W |

Photometrical data

| Luminous flux | 1600 lm |
|--------------------------|----------|
| Luminous efficacy | 106 lm/W |
| Color temperature | 2700 K |
| Color rendering index Ra | 90 |
| Light color | 927 |

Dimensions & Weight

| Overall length | 130.00 mm |
|----------------|-----------|
| Diameter | 70.00 mm |
| Product weight | 153.00 g |

Additional product data

| Base (standard designation) | E26 |
|-----------------------------|--------|
| Mercury content | 0.0 mg |

Capabilities

| Dimmable | Yes |
|----------|-----|
|----------|-----|

Country-specific categorizations

| Order reference | 15W/950 120V 4X |
|-----------------|-----------------|
| | |

Energy labelling regulation data acc EU 2019/2015

| Light source cap-type (or other electric interface) | E26 |
|---|-----------|
| Length | 130.00 mm |
| Height | 70.00 mm |
| Width | 70.00 mm |

Safety advice

- Suitable for use in dry and damp locations.
- -4°F to +104°F (-20°C to +40°C)

DOWNLOAD DATA

| Photometric and lighting design files | Document name |
|---------------------------------------|--------------------|
| IES file (IES) | LED15A21DIMO9SC3RP |

LOGISTICAL DATA

| Product code | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume |
|---------------|------------------------------|--------------------------------------|--------------|----------------------|
| 0046135421105 | Folding box 2 | 70 mm x 119 mm x 121 mm | 345.00 g | 1.01 dm ³ |
| 4058118285648 | Shipping box 8 | 311 mm x 139 mm x 135 mm | 1531.00 g | 5.84 dm ³ |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.