

PRODUCT DATASHEET

Dusk to Dawn 5CCT A19 12W DTD 5CCT 1PK

SYLVANIA Dusk to Dawn 5CCT Selectable A19 Lamps | 5CCT selectable A19 lamps with dusk to dawn sensor for automatic on/off lighting



Areas of application

- Driveways, backyards, parking lots, and porches in both residential and commercial applications

Product features

- Selectable CCTs: 2700/3000/3500/4000/5000K
- Toggle switch located on the lamp to change between CCTs in the field
- 15,000 hours lifetime (L70)
- No need to manually turn on/off the lights
- Automatically turns the light on in low-light conditions and back off when light is detected

TECHNICAL DATA

Electrical data

Nominal wattage	12 W
Construction wattage	12.00 W
Nominal voltage	120 V
Claimed equiv. conventional lamp power	100 W

Photometrical data

Luminous flux	1600 lm
Luminous efficacy	133 lm/W
Color temperature	2700 K
Color rendering index Ra	> 80
Light color	827

Dimensions & Weight

Overall length	118.00 mm
Diameter	65.00 mm
Product weight	56.2 g

Additional product data

Base (standard designation)	E26
Mercury content	0.0 mg

Capabilities

Dimmable	No
----------	----

Country-specific categorizations

Order reference	12W 120V 6X1 EN
-----------------	-----------------

Energy labelling regulation data acc EU 2019/2015

Light source cap-type (or other electric interface)	E26
Length	118.00 mm
Height	65.00 mm
Width	65.00 mm

Safety advice

- Suitable for damp locations – not for use where directly exposed to water.
- Not for use in dimming applications.
- Not for use with emergency light fixtures or exit lights.

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
0046135425646	Folding box 1	65 mm x 65 mm x 122 mm	88.00 g	0.52 dm ³
10046135425643	Shipping box 6	217 mm x 155 mm x 132 mm	695.00 g	4.44 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.