

PRODUCT DATASHEET Contractor Series Reflectors BR30 8W DIM 10YR 3500K 2PK

SYLVANIA Contactor Series Reflectors | Entry Level LED Reflectors



Areas of application

- Downlights, pendant fixtures, table lamps, wall sconces
- Healthcare, hospitality, residential, retail

Product features

- 11,000 hours lifetime (L70)
- CRI of 80 ensures good color definition
- No warm-up time, instant-on with full light output and stable color
- Dimmable down to 10 %



TECHNICAL DATA

Electrical data

Nominal wattage	8 W
Construction wattage	8.00 W
Nominal voltage	120 V
Claimed equiv. conventional lamp power	65 W
Type of current	AC
Operating frequency	5060 Hz
Mains frequency	5060 Hz

Photometrical data

Luminous flux	650 lm
Luminous efficacy	81 lm/W
Color temperature	5000 K
Color rendering index Ra	80
Light color	850

Dimensions & Weight

Overall length	127.00 mm
Diameter	95.00 mm
Product weight	80.00 g

Temperatures & operating conditions

Ambient temperature range	-20+45 °C
7 thorn tomporataro rango	201 10 0

Additional product data

Base (standard designation)	E26	
Mercury content	0.0 mg	
Mercury-free	Yes	
Product remark	All technical parameters apply to the entire lamp / Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value	

Capabilities

Dimmable Yes

Country-specific categorizations

	Order reference	8W/850 120V 6X2
--	-----------------	-----------------

Energy labelling regulation data acc EU 2019/2015

Light source cap-type (or other electric interface)	E26
Length	127.00 mm
Height	95.00 mm
Width	95.00 mm

Safety advice

- -4°F to +104°F (-20°C to +40°C)
- Not for use with emergency light fixtures or exit lights.
- Not for use in totally enclosed fixtures.

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
0046135780295	Folding box 2	95 mm x 165 mm x 137 mm	242.00 g	2.15 dm ³
10046135780292	Shipping box 12	352 mm x 311 mm x 141 mm	1782.00 g	15.49 dm³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.